

7 6 5 4 3 2 1

VIEW ON MATING SIDE

u	C	C	C	C	C	C	C	C	C	C	C
D	B	B									
o	A	A	A	A	A	A	A	A	A	A	A

16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1

A = 9 STANDARD CONTACTS L = 3
 B = 2 STANDARD CONTACTS L = 3
 C = 9 STANDARD CONTACTS L = 3
 S = 20 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0002 SHT 1

C	G2/0	c1,3,5....13, c15,16
B	G2/0	b14, b16
A	G2/0	a1,3,5....13, a15,16
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO: 12004-0325 DRWN: SHIVASHAZ004/02/23 CHKD: SUDHIR 2004/02/23 APPR: GJLOWE 2004/04/26	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION REVISE ON CAD ONLY	
		= 0 = 0	mm	INCH	DIMENSION STYLE MM ONLY			TITLE
			4 PLACES	± ---	± ---	DRAWN BY SHIVA	DATE 2004/02/23	48 POS MALE CONNECTOR ACC. DIN 41612 STYLE C/2 CONTACTS ARRANGEMENT MOLEX INCORPORATED
			3 PLACES	± ---	± ---	CHECKED BY SUDHIR	DATE 2004/02/23	
			2 PLACES	± ---	± ---	APPROVED BY GJLOWE	DATE 2004/02/23	
1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DOCUMENT NO. SD-85003-9039			
					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 1 OF 1	

6 5 4 3 2 1