


## NOTES:

- 1. MATERIAL AND FLAMMABILITY RATING.
  BODY -PC LIGHT GRAY POLYCARBONATE UL94-5VA
  COVER PC LIGHT GRAY POLYCARBONATE UL94-5VA
  CLEAR COVER (C) PC CLEAR POLYCARBONATE UL94-V0 AND TESED
  TO PASS 5VA PER UL746C
- 2. FOLLOW ENCLOSED INSTRUCTION FOR UL COMPLIANCE.: BOXES UL LISTED NEMA TYPE 1, 2, 3, 3R, 4, 4X, 5, 6, 6P 12, 13. DESIGNED MEETS IP65, IP66, IP67, IP68 REQUIREMENTS. UV RESISTANT FOR OUT DOOR USE.
- 3. OPERATING TEMPERATURE IS -35 TO 110C.
- 4. PRE INSTALLED SILICONE GASKET IN COVER
- 5. BOX COMES WITH 4 UNINSTALLED MOUNTING BRACKETS AND HARDWARE (DPX-100)
- 6. OPTIONAL ACCESSORIES:
  - HINGE AND PANEL SUPPENSION KIT (DPX-444KIT)
  - 6" FLANGE KIT (2 FLANGES + 4 SCREWS) (DPX-624KIT)
  - FLOATING INTERNAL MOUNTING PANEL (DPX-287084)
  - HINGED INTERNAL MOUNTING PANEL (DPX-287082)
  - COVER MOUNTING PANEL (DPX-287083)
  - BASE INTERNAL MOUNTING PANEL (DPX-287081)
- 7. DIMENSIONS ARE INCH



## **DRAWING FOR REFERENCE**

WE RESERVE THE RIGHT TO MAKE CHANGES TO OUR STANDARD PRODUCTS. PLEASE CONSULT WITH BUD INDUSTRIES PRIOR TO USING THIS DRAWING FOR DESIGN PURPOSE.

