	10		9	8	7		6		5	4		3
F	PAR NUMB 1300680	BER	NGINEERING NUMBER 1C4130-001									
E	NDTE:		2-1	GREEN/YELLOW -	1 3/8-16	UN-2A- 3-RED 4				34" REF		4-GF
D	1) LABEI VOL 2) ELEC REDU POLE MAX.	TAGE & TRICAL JCING A IS: 4 VOLTA	DAPTER QC T⊡ MC GE: 600∨ AC/DC	TE CODE, 1-BLACK	4	-WHITE				-8		
С	PROT TEMF 3) PACK ASSE POLY ATTA	AGING: IMBLIES 'BAGS ACHED T		RATELY IN BEL	1.5	17″ REF						
В	5) CERT	IFICATI		LE E258922 PLASTIC FILM	BLACK/YELLOW		<u></u>)	5
	7 6	4 N 1 N	MC SOCKET CONTACT MC INSERT	COPPER ALLOY	GOLD PLATED BLACK		0/01/12 0/01/15	QUALITY SYMBOLS		L TOLERANCES S SPECIFIED)		ENSION STYLE IN/MM DATE
A	5 4 3 2 1 ITEM	4 0 1 0 1 0 1 0	MC COUPLING NUT QC PIN CONTACT QC INSERT QC COUPLING NUT OVERMOLD DESCRIPTION	ZINC ALLOY COPPER ALLOY PVC ALUMINUM PVC MATERIAL	BLACK E-COAT GOLD PLATED BLACK BLACK ANODIZE GRAY FINISH		RELEASED EC NO: WNA2010-0424 DRWN: KJOZWIK 2010/01/12 CH*KD: BWOODMAN APPR: JFMURPHY 2010/01/15		3 PLACES 2 PLACES 1 PLACE ANGU DRAFT WHI MUS	mm INCH ± ± ±0.13 ±.010 ±0.25 ±.020 JLAR ±1/2° ERE APPLICABLE TREMAIN DIMENSIONS	KJOZWIK CHECKED BY BWOODM APPROVED B JFMURPH MATERIAL NC SEE	Z 2010/ DATE MAN 2010/ Y DATE HY 2010/
	10		9	8	7		6		5	4		3

