

# BFS60 Series

60 WATT UNREGULATED POWER SUPPLY

## Features

- Open frame
- Fully isolated output
- Input/output isolation: 1500VAC



Elpac Model	Vdc	Amps	Watts (max)	No Load (V)	Full Load (V)
BFS60-12	12	4.8	60	16.8	12.2
BFS60-20	20	3	60	25.8	19.8
BFS60-24	24	2.4	60	34.5	26.5
BFS60-48	48	1.2	60	62	48

## Specifications

### Input

- Voltage: 105/115/125 VAC
- Frequency: 47 – 440 Hz

### Output

- Unregulated:  $\pm 10\%$  full load
- Ripple/noise:  $\pm 3\%$  RMS, DC to 50MHz

### Environmental

- Operating temperature: 0°C to 40°C
- Storage temperature: -55°C to 85°C

### Mechanical

- Size: 6.3 x 3.0 x 3.7 inches

### Safety

- UL recognized



## ELPAC POWER SYSTEMS

1562 Reynolds Ave • Irvine CA, 92614  
Phone: (949) 476-6070 Fax: (949) 476-6075  
Toll free: (888) ELPAC80  
E-mail: sales@elpac.com or engr@elpac.com

[www.elpac.com](http://www.elpac.com)