

PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 25489, SO	04/21/14	HM
B	CLARIFY VIEW 'A' POLARITY RECEPTACLE 'LINE' AND 'NEUTRAL', RFS.27322	04/25/19	HM



'A'



'B'



GENERAL SPECIFICATIONS:

RATING: 10A / 250V AC
 CABLE TYPE / SIZE: SVT, # 18 AWG, 3 CONDUCTOR
 SHIELDED/ EUROPEAN COLOR CODED CONDUCTORS
 TEMPERATURE RATING: 75° C MINIMUM
 CONDUCTOR COLORS: BLUE / BROWN / GREEN-YELLOW
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH: 1830 ± 25 mm
 CABLE OUTER DIAMETER: 6.3 ± 0.1 mm
 END 'A' PLUG: IEC-320 / C13
 END 'B' : SEE TERMINATION TABLE
 APPROVALS PLUG: UL, CSA or cUL
 APPROVALS CABLE: UL, CSA or cUL



PACKING:

BULK PACKED, BUNDLES OF 25.
 MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

CONDUCTOR TERMINATION TABLE:

Wire	Color	ROJ ± 5 mm	RIJ ± 0.5 mm	Termination
Neutral	Bue	51	16	Stripped
Line	Brown	51	16	Stripped
Ground	Green-Yellow	51	16	Stripped

NOTES:

1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS AND/ OR FILE NUMBERS.
2. SHIELD IS CONNECTED TO GROUND PIN ON IEC 320/C13.



RELEASED
 By N.Frost at 3:33 pm, Apr 25, 2019

DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
		TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		GlobTek, Inc. www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
		MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY: SO	DATE: 04/21/14	DWG TITLE: NON-DETACHABLE CORDSET		
DRAWN: NF	DATE: 04/21/14	FSCN No.: G, CC	SIZE: A	REV. B
APRVD: HM	DATE: 04/21/14	SCALE: NONE	PART NO: 7011876F000-CEE(R)	SHEET 1/1

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice