HellermannTyton

Specification Sheet

Part Number: SNP101GHS0X2

Installation and removal can be five times faster than conventional clamps

Heat stabilized material is suitable for high temperature applications.

Completely reusable

Will not rust or corrode

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place

One-hand installation for tight places.

Snapper Hose Clamp, 4.12"-4.72" Bundle Diameter, PA66GF13, Black, 25/pkg

Article Number

190-00053

Туре

SNP101

Color

Black (BK)



Quantity Per	bag
Product Description	The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. They are manufactured in black PA66 glass filled, impact modified, heat stabilized material. Custom design and color options are available based upon application and volume requirements.
Short Description	Snapper Hose Clamp, 4.12"–4.72" Bundle Diameter, PA66GF13, Black, 25/pkg
Global Part Name	SNP101-PA66GF13-BK
Fixation Method	Plug-in mounting
Variant	Closed
Bundle Diameter Min (Imperial)	4.1
Bundle Diameter Min (Metric)	104.7
Bundle Diameter Max (Imperial)	4.7
Bundle Diameter Max (Metric)	119.0
Wall Thickness WT (Imperial)	.099
Wall Thickness WT (Metric)	2.525

Material	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
Material Shortcut	PA66GF13
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988

© 2022 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions