



Materials and Finish

Shell: Copper Alloy,
Plating - Matte Tin

Insulator: UL94V-0 Rated
PA6T Thermoplastic
Color - Black

Contacts: Phosphor Bronze
Plating - 30u" Gold
on Contact Area,
3.8um (150u") Matte Tin
on Solder Tail, all over
1.27um (50u") Nickel

Durability: 5000 mating cycles

Electrical Specifications

Rated Voltage:
30V AC (rms)

Contact Current Rating:
1A Max.

Contact Resistance:
50 milliohms Max.

Insulation Resistance:
1000 Megohms Min.

Dielectric Withstanding:
100V AC

Operating Temperature:
-55°C to +85°C

Mylar tape withstanding Temp
up to 280°C



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A3	03/14/08	ECO #08-021	R. Aguirre	H. MA	R. Aguirre	08/18/06
A4	09/14/09	ECO #09-070	S. Vien	H. MA		
A5	04/26/13	ECO #13-019	W. Cook	P. DalCanto		
A6	11/05/13	ECO #13-081	D. Gih	H. MA	UNITS	mm
A7	07/06/18	Update Address & RoHS	C. Kelleher	C. Furumasu		
A8	12/07/18	ECO #18-063	G. Serrato	D. Shehan		

KMBX-SMT5S-S30TRMT

USB, Mini-B Type Socket, RoHS Compliant

5-pin, SMT with Mylar Tape, USB 2.0, Tape and Reel

