ATGBICS QFX-SFP-DAC-3M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (3m, Passive)

Brand : ATGBICS

Product code: QFX-SFP-DAC-3M-C

Product name : QFX-SFP-DAC-3M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (3m, Passive)

QFX-SFP-DAC-3M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (3m, Passive)

ATGBICS QFX-SFP-DAC-3M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (3m, Passive):

ATGBICS QFX-SFP-DAC-3M compatible 10GBase-CU SFP+ to SFP+ direct attach cable operates over passive copper with a cable length of 3m. It is suitable for short reach connection between two SFP+ ports in 10G interconnecting networking applications. Our productmeets the specification of Juniper QFX-SFP-DAC-3M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 1x InfiniBand QDR, DDR, SDR, 10G Gigabit Ethernet, Fibre Channel, MSA SPF+ SFF-8431, SFF-8432, and SFF-8472 compliant.

ATGBICS QFX-SFP-DAC-3M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (3m, Passive). Cable length: 3 m, Connector 1: SFP+, Connector 2: SFP+, Data transfer rate: 10000 Mbit/s







Features		Features	
Product colour * Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Jacket material	Black 3 m SFP+ SFP+ Male Male Polyvinyl chloride (PVC) Copper 10 Gigabit Ethernet IEEE 802.3ae 30 10000 Mbit/s ✓ CE, FCC, RoHS	Country of origin Brand compatibility Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	China Juniper 0 - 70 °C -40 - 80 °C 10 - 90% 10 - 85%
Conductor material Ethernet interface type Networking standards AWG wire size Data transfer rate Plug and Play Certification		Packaging dataQuantity per packTechnical detailsSustainability complianceSustainability certificatesDoesn't contain	1 pc(s) ✓ RoHS Lead



5056468721778

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.