

## Han 3A RJ45 plug insert 4p IDC AWG 26




Image is for illustration purposes only. Please refer to product description.

Part number	09 45 100 1110
Specification	Han 3A RJ45 plug insert 4p IDC AWG 26
HARTING eCatalogue	<a href="https://b2b.harting.com/09451001110">https://b2b.harting.com/09451001110</a>

### Identification

Category	Connectors
Series	RJ45
Element	Cable connector
Specification	RJ45

### Version

Termination method	IDC termination
Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4
Pack contents	Connector insert

### Technical characteristics

Conductor cross-section	0.12 mm <sup>2</sup> Stranded
Conductor cross-section	AWG 26 Stranded
Wire outer diameter	1.6 mm
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Cable diameter	6.5 ... 9.5 mm



Pushing Performance  
Since 1945

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	EN 45545-2
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	40.7 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140058675
eCl@ss	27440205 Contact insert for industrial connectors