# S200 Master - Duino Zero



| | | |
|---|---|---|
| **Title:** 01. Index.SchDoc | | rhomb Modular System |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 1 of 8 | |

# S200 Master - Duino Zero







| | | |
|---|---|---|
| **Title:** 02. Block Diagram.SchDoc | | |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 2 of 8 | |

rhomb
Modular System

# S200a MASTER - PLUG

Transparent TOP VIEW










DESIGN NOTE:
- I2C pull-up resistors are placed on the motherboard, not on the module.
- UART, CAN & SAI lines are crossed on the motherboard, not on the module.
- The text of the unnused nets have been deleted.
- VIO_IN provides the voltage reference with which the Core operates.











| | |
|---|---|
| **Title:** 03. S200a Master - Plug.SchDoc | |
| **Engineer:** J.Park | **Date:** 08/02/2019 |
| **Project:** S200 Master - Duino Zero.PrjPcb | |
| **Revision:** v1.0 | **Sheet:** 3 of 8 |

rhomb
Modular System

# S200b MASTER - PLUG

Transparent TOP VIEW




| | | |
|---|---|---|
| **Title:** 04. S200b Master - Plug.SchDoc | | |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 4 of 8 | |

rhomb.io
Free to Create

# MCU ATSAMD21G18A




| | |
|---|---|
| **Title:** 06. MCU ATSAMD21G18A.SchDoc | |
| **Engineer:** J.Park | **Date:** 08/02/2019 |
| **Project:** S200 Master - Duino Zero.PrjPcb | |
| **Revision:** v1.0 | **Sheet:** 5 of 8 |

rhomb Modular System

## MUX DIG/ANA




## DEGUB CONNECTOR




## POWER SUPPLY SELECTION




## USER LED & TEST PADS




| | | |
|---|---|---|
| **Title:** 05. Power & Connections.SchDoc | | |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 5 of 8 | |

rhomb
Modular System

## SECURITY




Supply IO levels from 1.8V to 5.5V

## SPI MEMORY




Supply voltage range from 1.65V to 3.6V
Master Module is limited to 3.6V
because it's me Vmax supported by SPI memory

| | | |
|---|---|---|
| **Title:** 07. Memories.SchDoc | | rhomb Modular System |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 6 of 8 | |

## PCB

A_PCB

S200 Master
Duino Zero

RLRHMDUINOZERO101807

## TOP LAYER FIDUCIALS




SECONDARY FIDUCIAL


SECONDARY FIDUCIAL


MAIN FIDUCIAL

## BOTTOM LAYER FIDUCIALS




SECONDARY FIDUCIAL


SECONDARY FIDUCIAL


MAIN FIDUCIAL

## ID EEPROM




| | | |
|---|---|---|
| **Title:** 08. Production.SchDoc | | |
| **Engineer:** J.Park | **Date:** 08/02/2019 | |
| **Project:** S200 Master - Duino Zero.PrjPcb | | |
| **Revision:** v1.0 | **Sheet:** 7 of 8 | |

rhomb
Modular System