

## INCA®-IP2

Single-chip IP Phone with Internal  
GbESwitch  
PSB 21653E



INCA®-IP2 is Infineon's second generation of IP Phone terminal chips, and the 5th generation of PBX phone devices. Enabled by two powerful 400 MHz MIPS CPU's and an internal Gigabit Ethernet switch it represents a quantum leap for IP Phones in the Telecommunication network. Typically an IP Phone is not the end point of the IP network's architecture and as such should not represent a bottleneck for a Gigabit Ethernet Network. INCA-IP2's dual core approach offers a tremendous opportunity to IP Phone manufacturers to differentiate their phones in an increasingly competitive environment. The INCA-IP2's powerful engine turns the IP Phone into an IP appliance enabling a slew of voice and multimedia features, making it possible to offer low to high end phones based on one platform. Phone makers can consider adding AMR, LEC, AEC, T.38, MP3 decoding, MiDi Synthesizer and even streaming video to their feature sets.

### CPU Features

- 400 MHz MIPS 24KEc CPU
- 16kB Instruction and 16kB Data Cache
- DDR-SDRAM Controller, NAND and NOR Flash support
- Support for 16 bit instruction encoding (MIPS16e ASE) for code size reduction

### Voice Processing Features

- 400 MHz MIPS 24KEc voice engine with DSP application specific extensions
- Voice Coding G.711, G.723.1, G.729A/B, G.722, G.722.1, iLBC, AMR,
- Two D/A and A/D converters for in call announcements and other applications
- Advanced acoustic echo cancellation for full duplex speakerphone, three-party conferencing with mixed codecs
  - Handset echo cancellation
  - Voice Activity Detection
  - Speech Recognition

### Ethernet Features

- Full 3 port Gigabit Ethernet Switch with two GMACs and RGMII interface for optional connection of external GPHYs
- Two integrated 10/100BaseT Ethernet MACs and PHYs for LAN and PC connection
- 802.1p & Q standard compliant
- Sophisticated Policy and Flow Engine supporting up to 24 flows, based on L2 to L7 information, allowing leading edge traffic classification
- Flexible Traffic Management

- Support for up to 4 priority queues, enabling time-sensitive data to have access to the network with minimal delay

### Interfaces and Ports

- USB2.0 Full/Low Speed Host
- Two SSC (synchronous serial interface), SPI compatible,
- EBU: parallel 8/16 Bit Interface
- PCM interface including FIFO, AC97 codec interface
- Memory controller supporting SDR and DDR1 SDRAM
- Two ASC/UART supporting IrDA
- Under voltage detection (UVD) with power on reset functionality saves external POR
- Real time clock (RTC), optionally with separate oscillator connection for low power mode

### Data Encryption Unit

- Powerful HW-accelerator to support encryption
- (DES/3DES, AES) and hashing (SHA-1, MD5)
- True Random Number generator
- 802.1x Authentication

### Applications

- IP Phones and Video Phones
- WLAN base-stations
- Network Fax Machines


[www.infineon.com/voip](http://www.infineon.com/voip)

## Communication Solutions



Never stop thinking

## INCA - IP2 Block Diagram




## Software

The INCA-IP2 comes with a complete SIP Phone HW and SW reference design using Infineon-developed software. This includes a comprehensive set of voice codecs, as well as network, SIP Protocol and VoIP related features. In addition developers will be familiar with the EASY 21653 Board support package with a complete set of device drivers, Linux kernel 2.4.2 as well as a HW reference design with full acoustic support

## Application Example

Gigabit Ethernet Enterprise IP - Phone



## Product Summary

Type	Sales Code	Description	Package
INCA-IP2	PSB 21653 E	Single-chip IP phone with integrated GbE switch	PG-LBGA-324-3
EASY 21653	EASY 21653	INCA-IP2 IP-phone evaluation and demonstration board	

How to reach us:  
<http://www.infineon.com>

Published by  
**Infineon Technologies AG**  
 81726 Munich, Germany

© 2007 Infineon Technologies AG  
 All Rights Reserved.

### Legal Disclaimer

The information given in this Product Brief shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

### Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

### Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.