

OMNI™ Occupancy Sensors

Ceiling Mount Sensors featuring IntelliDAPT™

OVERVIEW

OMNI ceiling mount occupancy sensors employ a combination of passive infrared, ultrasonic and IntelliDAPT technologies to provide unequalled occupancy detection and false trip immunity. OMNI sensors are available with optional relay control for use with Building Automation Systems, and a photosensor for automatic daylight harvesting.

FEATURES

- IntelliDAPT technology
- Non-volatile memory for sensor settings
- Coverage up to 2,000 sq. ft. (depending on model)
- Optional relay and photocell control
- Optional Quick To Install (QTI) connector



OMNIDT | OMNIDTRP

OCCUPANCY SENSORS

ORDERING INFORMATION

OMNI				
MODEL	TECHNOLOGY	COVERAGE	RELAY/PHOTOCELL OPTION	QTI
OMNI	DT Dual Technology US Ultrasonic IR Passive Infrared DIA Dual Technology Acoustic & Passive Infrared	500 500 sq. ft. 1000 1,000 sq. ft. 2000 2,000 sq. ft. L Long Range IR	RP Relay & Photocell Blank No Option	QTI Quick to Install Blank No QTI

ADDITIONAL PRODUCT IMAGES



OMNIUS | OMNIUSR




OMNIIR | OMNIIRP




OMNIDIA | OMNIDIARP


DIMENSIONS




OMNIDT2000
Range Diagram




OMNIUS500
Range Diagram




OMNIIR
Range Diagram




OMNIDIA
Range Diagram




OMNIDT500
Range Diagram




OMNIUS2000
Range Diagram



OMNIDT500
Range Diagram



OMNIDT1000 — Range Diagram



OMNIUS2000 hallway
Range Diagram



Building Automation, Inc.