

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

Q	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	X	X	X				
Q	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	Z	Z	Z				
	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1

A = 29 STANDARD CONTACTS L = 3
 C = 29 STANDARD CONTACTS L = 3
 Z = 3 FMLB CONTACTS +0,6 L = 3
 X = 3 FMLB CONTACTS +0,6 L = 3
 S = 64 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL 2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

X	G2/O	c1,2,3
Z	G2/O	a1,2,3
C	G2/O	c4-32
A	G2/O	a4-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO.1 2004-XXXX DRAWN N.S. 09/09/03 CHK'd G.L. 09/09/03 APPR G.L. 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	DIMENSIONS:	SHT	REV
	MAJOR			<input type="checkbox"/> MM <input checked="" type="checkbox"/> INCH	<input type="checkbox"/> MM <input type="checkbox"/> INCH <input checked="" type="checkbox"/> MM ONLY		REVISE ON CAD ONLY
	CRITICAL	4 PLACES ±0. ±.		DRAWN BY & DATE N.S. 08/03/01	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT		
		3 PLACES ±0. ±.		CHECKED BY & DATE G.L. 08/03/01	MOLEX MOLEX INCORPORATED		
	2 PLACES ±0. ±.		APPROVED BY & DATE G.L. 08/03/01	CAD FILENAME SD-85003-1457.S0	MATERIAL NO. 85003-1457	DRAWING NO. SD-85003-1457	SHEET NO. 1 OF 1
	1 PLACE ±0. ±.		ANGULAR ±	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
				SIZE D			

24-border.DGN REV A 96/06/12 LEVEL 6 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1