

# General Electronic Devices

Makers of active and passive components  
 Quartz Crystal \* Oscillators \* Synthesizer \* Filters  
 Micro-Hybrid Assembly Services


## SMD100B-ED-32.768KHz

### 1. ELECTRICAL CHARACTERISTICS


Parameter	Value
Holder Style	7.0x5.0mm SMD oscillator
Frequency	32.768KHz
Frequency stability ( Stability vs temp,vs supply variations,vs load variations,calibration & aging)	$\pm 50$ ppm
Supply Voltage	$5.0 \pm 10\%$ VDC
Output waveform	CMOS
Operating Temp. Range	-10~70°C
Storage Temp.Range	-55~+125°C
Symmetry	45%/55%(min/max)
Output load	15pF
Standby Current Consumption	10uA (max)
Start up time	5ms (max)
Rise/Fall time	45ns( max)
Aging	$\pm 5$ ppm(@25°C 1 <sup>st</sup> year)

### 2. DIMENSION:(unit:mm)


[TOP VIEW]



[BOTTOM VIEW]



[SIDE VIEW]



Pin#	Function
1	Enable Control
2	GND
3	Output
4	VDD



# General Electronic Devices

Makers of active and passive components  
Quartz Crystal \* Oscillators \* Synthesizer\* Filters  
Micro-Hybrid Assembly Services

