

Data sheet**Flush mount built-in outlet gray**

Page 1/4

P/N

1309441903-I

EAN 4015394048176

2022/07/15

Version: A

Illustrations

See enlarged drawings at the end of document

Product specification

- UP installation outlet for flush mounting of the IP44SG UP housing



P | Cabling

Data sheet

Page 2/4

Flush mount built-in outlet gray

P/N

1309441903-I

EAN 4015394048176

2022/07/15

Version: A

Technical Data

General Data

Fields of application	office areas
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	UP
Color	gray

Materials and material properties

Halogen free	yes
Silicone free	no paint wetting interfering substances (LaBS) in the process chain
LaBS Note	subsequent contamination possible due to handling and possible storage in your company
RoHS	compliant
REACH	compliant

Environmental conditions

Particulate ingress	IP4X
Liquid ingress/immersion	IPX4

Standards/Regulations

Cover plates for installation devices 1	DIN 49075-1:1989-10
Cover plates for installation devices 2	DIN 49075-2:1989-10

Classifications

ETIM 5.0	EC000766
ETIM 6.0	EC000766
ETIM 7.0	EC000119
ETIM 8.0	EC000119

P | Cabling

Data sheet

Page 3/4

Flush mount built-in outlet gray

P/N

1309441903-I

EAN 4015394048176

2022/07/15

Version: A

Technical Data

Packing details

Type of packaging	1 pc(s) / plastic bag
Packaging unit - Weight (gram)	762 g
Packaging unit - Weight (pound)	1.68 lb
Packaging dimension	300 mm x 200 mm x 50 mm
Packaging dimension	11.811 in. x 7.874 in. x 1.969 in.

P | Cabling

Data sheet

Page 4/4

Flush mount built-in outlet gray

P/N

1309441903-I

EAN 4015394048176

2022/07/15

Version: A

Accessories from

P/N	Designation
1309461002-I	E-DAT modul IP44SG UP housing pure white unequipped
1309461003-I	E-DAT modul IP44SG UP housing gray unequipped

