


Features

- Waterproof construction.
- Suitable for outdoor applications, signboard or message board, etc.
- RoHS compliant.



Package Schematics



Electrical / Optical Characteristics at TA=25°C

Symbol	Parameter	Device	Min.	Typ.	Max.	Units	Test Conditions
I _v	Luminous Intensity CIE127-2007*	XK50DGKW89	175000*	244990*	-	mcd	I _F =200mA
2 θ _{1/2}	Viewing Angle		-	40	-	deg	-
V _F	Forward Voltage		-	16.5	20.5	V	I _F =200mA
λ _P	Peak Wavelength CIE127-2007*		-	515*	-	nm	I _F =200mA
λ _D	Dominant Wavelength CIE127-2007*		-	525*	-	nm	I _F =200mA
Δλ _{1/2}	Spectral Line Half-width		-	35	-	nm	I _F =200mA
I _R	Reverse Current		-	-	100	uA	V _R = 5V



Note:



*Luminous intensity value and wavelength are in accordance with CIE127-2007 standards.

Absolute Maximum Ratings at TA=25°C

Parameter	Type	Units
Power dissipation	5125	mW
DC Forward Current	250	mA
Reverse Voltage	5	V
Electrostatic Discharge Threshold (HBM)	450	V
Operating Temperature	-40°C To +70°C	
Storage Temperature	-40°C To +85°C	

PACKING & LABEL SPECIFICATIONS



		<table border="1"> <tr> <td>Q.C.</td> <td>Q C</td> </tr> <tr> <td>XX</td> <td>XX XX</td> </tr> <tr> <td colspan="2" style="text-align: center;">PASSED</td> </tr> </table>	Q.C.	Q C	XX	XX XX	PASSED	
Q.C.	Q C							
XX	XX XX							
PASSED								
P/NO : XK50xxx								
QTY : 1 pcs		CODE: XXX						
S/N : XX								
LOT NO:								
 xxxxxxxxxxxxxxxxxxxxxxxx								
RoHS Compliant								

TERMS OF USE

1. Data presented in this document reflect statistical figures and should be treated as technical reference only.
2. Contents within this document are subject to improvement and enhancement changes without notice.
3. The product(s) in this document are designed to be operated within the electrical and environmental specifications indicated on the datasheet. User accepts full risk and responsibility when operating the product(s) beyond their intended specifications.
4. The product(s) described in this document are intended for electronic applications in which a person's life is not reliant upon the LED. Please consult with a SunLED representative for special applications where the LED may have a direct impact on a person's life.
5. The contents within this document may not be altered without prior consent by SunLED.
6. Additional technical notes are available at <http://www.SunLEDusa.com/TechnicalNotes.asp>