



Precision ESD Safe TORX® Drivers



278 TORX® Screwdriver, With Precision ESD Safe Dissipative Handle. Blade high alloy CVM steel. Hard chrome finished. Handle impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item	Star Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
278 01	T1	40	1.6	120	4.7	.03	10
278 02	T2	40	1.6	120	4.7	.03	10
278 03	T3	40	1.6	120	4.7	.03	10
278 04	T4	40	1.6	120	4.7	.03	10
278 05	T5	40	1.6	120	4.7	.03	10
278 11	T6	40	1.6	120	4.7	.03	10
278 17	T7	40	1.6	120	4.7	.03	10
278 23	T8	40	1.6	120	4.7	.03	10
278 29	T9	50	2.0	145	5.7	.04	10
278 35	T10	50	2.0	145	5.7	.04	10
278 41	T15	60	2.4	170	6.7	.07	10
278 47	T20	60	2.4	170	6.7	.07	10

*Metric dimensions actual - Inch dimensions approximate



ESD standard
IEC 61340-5-1



278 90 Set 7 Pcs. TORX® Precision ESD Safe Dissipative Handle
Blade high alloy CVM steel, hardened, hard chromed. Handle manufactured from impact resistant, dissipative material.

Item	Star Icon	Hex Icon	Star Icon	Hex Icon	Hex Icon		
No.	Size	mm	Size	mm	lbs.		
278 90	278 04	T4	40	278 23	T8	40	.31
	278 05	T5	40	278 29	T9	50	
	278 11	T6	40	278 35	T10	50	
	278 17	T7	40				




ESD standard
IEC 61340-5-1



278 99 Set 8 Pcs. TORX® Precision ESD Safe Dissipative Handle Set In Pouch
Blade high alloy CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material.

Item	Star Icon	Hex Icon	Star Icon	Hex Icon	Hex Icon		
No.	Size	mm	Size	mm	lbs.		
278 99	278 01	T1	40	278 05	T5	40	.30
	278 02	T2	40	278 06	T6	40	
	278 03	T3	40	278 07	T7	40	
	278 04	T4	40	279 20	Chip Lifter		

Precision ESD Safe TORXPlus® Drivers



278 TORXPlus® Screwdriver, With Precision ESD Safe Dissipative Handle. Blade high alloy CVM steel, hardened, hard chromed. Handle impact resistant, dissipative material. ESD standard IEC 61340-5-1

Item	Star Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon	Hex Icon
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
278 50	IP4	40	1.6	120	4.7	.03	10
278 51	IP5	40	1.6	120	4.7	.03	10
278 52	IP6	40	1.6	120	4.7	.03	10
278 53	IP7	40	1.6	120	4.7	.03	10
278 54	IP8	40	1.6	120	4.7	.03	10
278 55	IP9	50	2.0	145	5.7	.04	10
278 56	IP10	50	2.0	145	5.7	.04	10
278 57	IP15	60	2.4	170	6.7	.07	10

*Metric dimensions actual - Inch dimensions approximate



ESD standard
IEC 61340-5-1



278 94 Set 7 Pcs. TORXPlus® Precision ESD Safe Dissipative Handle
Blade high alloy CVM steel, hardened, hard chromed.

Item	Star Icon	Hex Icon	Star Icon	Hex Icon	Hex Icon		
No.	Size	mm	Size	mm	lbs.		
278 94	278 51	IP5	40	278 55	IP9	50	.32
	278 52	IP6	40	278 56	IP10	50	
	278 53	IP7	40	278 57	IP15	60	
	278 54	IP8	40				

