

C30884EH

Silicon Avalanche Photodiode With Very High Modulation Capability



The C30884EH is a silicon avalanche photodiode having high responsivity and fast rise and fall times. Because the fall time characteristic has no “tail”, the responsivity of the device is independent of modulation frequency up to about 400 MHz.

This device is made using a double-diffused “reach-through” structure and is optimized for high responsivity at wavelengths of below 1000 nanometers.

The C30884EH is hermetically sealed behind a flat glass window in a modified low-profile TO-5 package.

The fast time response characteristics and high responsivity of this device make it highly useful in a wide variety of applications including optical communications, laser range finding and high-speed switching systems.

Key Features

- High Quantum Efficiency –
85% typical at 900 nm
10% typical at 1060nm
- Spectral Response Range–
(10% Points) 400 to 1100 nm
- Fast Time Response –
Rise time typically 1 ns
Fall time typically 1 ns
- Wide operating Temperature
Range –
-40°C to 70°C
- Hermetically Sealed Low-
Profile TO-5 package

Applications

- Optical Communications
- Laser Range Finding
- High Speed Switching Systems

Photodiode C30884E series

Silicon Avalanche Photodiode With Very High Modulation Capability

Table 1 – Mechanical and Optical Characteristics

Parameter	Symbol		Unit	Remarks/Conditions
Photosensitive Surface:				
Useful area	A	0.5	mm ²	Shape : Circular
Useful diameter	d	0.8	mm	
Field of View:				
Nominal field of view α (See Figure 7)	FoV	119	Degrees	
Nominal field of view α' (See Figure 7)		132		

Table 2 – Electro-Optical Characteristics

Test conditions: Case Temperature $T_A = 22\text{ }^\circ\text{C}$; at the DC reverse operating voltage V , V_{op} supplied with the device³

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Breakdown Voltage	V_{br}	190		290	V
Operating Voltage	V_{op}	180		260	V
Temperature Coefficient of V_{op} for Constant Gain ¹	V_{op}		1.1		V/ $^\circ\text{C}$
Gain	M		100		
Responsivity					
at 900 nm	R	55	63		A/W
at 1060 nm		6	8		
Quantum Efficiency					
at 900 nm	Q.E.		85		%
at 1060 nm			10		
Dark Current ²	I_d			75	nA
Noise Current $f=10\text{kHz}$, $\Delta f=1.0\text{Hz}$	i_n			1	pA/sqrt(Hz)
Rise/Fall Time, $R_L = 50\Omega$:					
10% to 90% points	t_r		1	1.5	ns
90% to 10% points	t_f		1	1.5	
Capacitance	C_d		4	6	pF
Series Resistance				15	Ω
Storage Temperature	T_{stg}	-60		100	$^\circ\text{C}$
Operating Temperature	T_o	-40		70	$^\circ\text{C}$

¹ For V_{br} at other temperatures, see Figures 2 and 3.

² See Figure 4.

³ Each individual APD is supplied with its own test data at shipment


Photodiode C30884E series

Silicon Avalanche Photodiode With Very High Modulation Capability

Table 3 – Maximum Ratings, Absolute Maximum Values

Parameter	Symbol	Maximum	Unit	Remarks/Conditions
Reverse Bias Dark Current		100	μA	
Photocurrent average value peak value	i_p	500 2	μA mA	For 1 second duration, non-repetitive.
Forward Current average value peak value	I_F	5 50	mA	For 1 second duration, non-repetitive.
Total power		0.1	W	Dissipation at 22°C

Figure 1 – Typical Spectral Responsivity Characteristics at a Gain of 100



Silicon Avalanche Photodiode With Very High Modulation Capability

Figure 2 – Typical Responsivity at 900 nm as a function of Operating Voltage, V_{op}





Figure 3 – Typical Responsivity at 1060 nm as a function of Operating Voltage, V_{op}



Silicon Avalanche Photodiode With Very High Modulation Capability

Figure 4 – Typical Dark Current as a function of Operating Voltage, V_{op}

Test conditions: Case temperature = 22°C





Figure 5 – Typical Gain as a function of Light Spot Position

Test conditions: Case temperature = 22°C, Detector center = 0, Spot diameter = 0.0254 mm



Silicon Avalanche Photodiode With Very High Modulation Capability

Figure 6 – Approximate field of view





Figure 7 – Dimensional Outline



Photodiode C30884E series

Silicon Avalanche Photodiode With Very High Modulation Capability

RoHS Compliance

The C30884EH is designed and built to be fully compliant with the European Union Directive 2011/65/EU – Restriction of the use of certain Hazardous Substances (RoHS) in Electrical and Electronic equipment.



Warranty

A standard 12-month warranty following shipment applies. Any warranty is null and void if the photodiode window has been opened.

About Excelitas Technologies

Excelitas Technologies is a global technology leader focused on delivering innovative, customized solutions to meet the lighting, detection and other high-performance technology needs of OEM customers.

Excelitas has a long and rich history of serving our OEM customer base with optoelectronic sensors and modules for more than 45 years beginning with PerkinElmer, EG&G, and RCA. The constant throughout has been our innovation and commitment to delivering the highest quality solutions to our customers worldwide.

From analytical instrumentation to clinical diagnostics, medical, industrial, safety and security, and aerospace and defense applications, Excelitas Technologies is committed to enabling our customers' success in their specialty end-markets. Excelitas Technologies has approximately 5,000 employees in North America, Europe and Asia, serving customers across the world.

Excelitas Technologies
22001 Dumberry Road
Vaudreuil-Dorion, Quebec
Canada J7V 8P7
Telephone: (+1) 450 424 3300
Toll-free: (+1) 800 775 6786
Fax: (+1) 450 424 3345
detection@excelitas.com

**Excelitas Technologies
GmbH & Co. KG**
Wenzel-Jaksch-Str. 31
D-65199 Wiesbaden
Germany
Telephone: (+49) 611 492 430
Fax: (+49) 611 492 165
detection.europe@excelitas.com

Excelitas Technologies Singapore, Pte. Ltd.
8 Tractor Road
Singapore 627969
Telephone: (+65) 6775 2022 (Main number)
Telephone: (+65) 6770 4366 (Customer Service)
Fax: (+65) 6778-1752
detection.asia@excelitas.com



For a complete listing of our global offices, visit www.excelitas.com/locations

© 2016 Excelitas Technologies Corp. All rights reserved. The Excelitas logo and design are registered trademarks of Excelitas Technologies Corp. All other trademarks not owned by Excelitas Technologies or its subsidiaries that are depicted herein are the property of their respective owners. Excelitas reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.