

## Specification Sheet

Part Number: TAG16T3-DTH



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, 0.90" x .25", 3 Across, PET, White, 10,000/roll

Article Number 596-00034

Type TAG16T3

Color White (WH)

Quantity Per roll

**Product Description**

HellermannTyton white polyolefin labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's polyolefin material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description	Thermal Transfer Labels, 0.90" x .25", 3 Across, PET, White, 10,000/roll
Global Part Name	TAG16T3-PO-WH
Width W (Imperial)	0.9
Width W (Metric)	22.86
Thickness T (Metric)	64.0
Height H (Imperial)	0.25
Height H (Metric)	6.35
Width of Liner (Metric)	85.09
Width of Liner (Imperial)	3.35
Material	Polyolefin (PO)
Material Shortcut	PO
Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-40°F to +140°F (-40°C to +60°C)

Operating Temperature -40°F to +140°F (-40°C to +60°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 10000

Package Quantity (Metric) 10000

Customs Number 3919102055

Labels per Column 1

Labels per Row 3