

## ICM24 / ICM30 Series

# 24W & 30W International Adapter

- DOE Level VI Efficiency Rating
- Universal Input: 90 ~ 264Vac, 47/63 Hz
- UL/cUL Safety Approved
- Corded Output Connection
- US, UK, AU and EU plug-in adapters
- Light Weight and Compact



Model No.	Application	Output Connector	Output Voltage	Output Current			Voltage Accuracy	Ripple Noise	Line Reg.	Load Reg.
				Min	Rated	Peak				
ICM24-120	UL/cUL 62368-1 AV/ITE	Corded Plug 5.5 x 2.1 x 9.5mm	+12.0V	0	2.0	—	±5%	100mVp-p Max.	±1%	±5%
ICM24-180			+18.0V	0	1.3	—				
ICM24-240			+24.0V	0	1.0	—				
ICM24-300			+30.0V	0	0.8	—				
ICM24-360			+36.0V	0	0.7	—				
ICM30-090			+9.0V	0	3.0	—				
ICM30-120			+12.0V	0	2.5	—				
ICM30-180			+18.0V	0	1.67	—				
ICM30-240			+24.0V	0	1.25	—				
ICM30-300			+30.0V	0	1.0	—				
ICM30-360			+36.0V	0	0.83	—				

- Output voltages from 12.0Vdc to 36.0Vdc are available in increments of 0.1V. Please contact Tri-Mag, LLC for the part number and specifications for your output voltage requirement and application.
- The output voltage is verified to specs at 60 percent rated load condition.
- The **line regulation** is defined by changing ± 10 percent of input voltage from the nominal line at rated load.
- The **load regulation** is defined by changing ± 40 percent of the measured output load from 60 percent of the rated load.
- The **ripple and noise** is measured by using 20MHz bandwidth limited oscilloscope with each output terminated with a 10 µF electrolytic and a 0.1 µF capacitor at rated load and nominal line.
- The **efficiency** is measured at rated load and nominal line.

# ICM24 / ICM30 Series

An innovative, reliable, and inexpensive international adapter. That's the ICM24/ICM30 Series.

This economical, UL/cUL 62368-1 approved, DOE Level VI compliant power supply/charger is rated up to 30W when powering stationary or charging portable devices.

Plenty of voltage levels to choose from, too. From 12.0Vdc all the way up to 36.0Vdc (in increments of 0.1V), to match your need.

Call us (800-657-0853) for the part number to match your specifications.

## Specifications

### Input

Input Voltage	• 90 Vac ~ 264 Vac
Input Frequency	• 47 Hz to 63 Hz
No Load Input Power	• < 0.1W
Input Current	• 1.2A Max.
Inrush Current	• 40A Max.
Leakage Current	• 0.25mA Max.
Input Connection	• US (others available)

### Output

Output Voltage Range	• 12.0 to 36.0 Vdc
Output Current Range	• ICM24: 667 - 3500mA, 24W Max. • ICM30: 833 - 3500mA, 30W Max.
Minimum Load	• No min. load required.
Line Regulation	• ± 1% at rated load across input voltage range
Load Regulation	• ± 5%
Ripple & Noise	• 100mVp-p Max.
Overvoltage Protection	• Auto recovery
Overload Protection	• Auto recovery
Short Circuit Protection	• Auto recovery

### General

Insulation Resistance	• 50MΩ Min.
Efficiency	• Level VI compliant
MTBF	• 50,000 hrs to MIL-HDBK-217F at +25°C

### Environmental

Operating Temperature	• 0°C to 40°C
Operating Humidity	• 5% - 95% RH, Non-Condensing
Storage Temperature	• -20°C to +80°C

### EMC & Safety

Safety Approvals	• UL: UL 62368-1 • cUL: cUL 62368-1
EMC Approvals	• FCC

### Warranty

Warranty Period	• 3 year
-----------------	----------

### Dimensions and Notes

Dimensions in mm	
Tolerance	• ± 0.2mm
Size	• 71.2 x 43.2 x 30.5 mm • 2.80 x 1.70 x 1.20 Inches
Weight	• Approx. 140g (4.9oz.)
Connectors	• AC input, US, UK, AU & EU adapters available • DC output, standard 5.5 x 2.1 x 9.5mm corded, center positive, dc output plug or per customer specification.
Cord length	• 1500 ± 20 mm (59 ± .8")

### Mechanical Drawing

