

## Protect It! 1-Outlet Portable Surge Protector, Direct Plug-In, 750 Joules, Tel/Modem Protection

MODEL NUMBER: TRAVELCUBE



### Highlights

- 1 AC outlet
- Direct plug-in design
- Built-in tel/modem surge protection
- 750 joule rating
- Diagnostic LED displays protection status

### Package Includes

- TRAVELCUBE surge suppressor

### Description

The TRAVELCUBE is designed for convenient portable and economical surge protection. Small and powerful, the TRAVELCUBE features 750 joules and carries \$10K of insurance as well as a lifetime product warranty. Throw it in a briefcase or purse and have quality surge protection wherever you need it — hotel room, dorm, client office — anywhere!

### Features

- Portable wall-mount cube stores easily in any bag or briefcase
- 1 NEMA5-15R AC outlet
- 750 joules of protection shields equipment from harmful surges, spikes and line noise
- Diagnostic LED displays protection status
- Built-in tel/modem surge protection
- UL 1449 rated 3rd Edition
- \$10,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

## Specifications

| OVERVIEW                           |                 |
|------------------------------------|-----------------|
| UPC Code                           | 037332118486    |
| INPUT                              |                 |
| Nominal Input Voltage(s) Supported | 120V AC         |
| Recommended Electrical Service     | 120V (110-125V) |



|  |  |
|--|--|
| Input Cord Length Details                    | Direct plug-in   |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 36000  |
| Input Plug Type                              | NEMA 5-15P   |
| Input Cord Length (ft.)                      | 0  |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 0.00   |
| Integrated Cord Clip                         | No   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output (Watts)                               | 1800   |
| Output Receptacles                           | (1) 5-15R  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | (1) Yes  |
| Right-Angle Outlets                          | Yes  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Diagnostic LED(s)                            | Yes  |
| Diagnostic LED Details                       | Built-in LED confirms suppressor "protection present" (red) status           |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 750  |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating                    | 500V   |
| EMI / RFI Filtering                          | Up to 20 dB  |
| Automatic Shut-Off                           | No   |
| <b>DATALINE SURGE SUPPRESSION</b>            |  |
| Telephone/DSL Protection Details             | 1 line   |
| Cable (Coax) Protection                      | No   |
| Network (Ethernet) Protection                | No   |
| Telephone/DSL Protection                     | Yes  |
| <b>PHYSICAL</b>                              |  |
| Material of Construction                     | Plastic  |



|  |  |
|--|--|
| Form Factors Supported                                     | Direct plug in suppressor supports wall-mounting directly into AC receptacle   |
| Housing Color  | Light Gray   |
| Mounting Holes or Slots                                    | No   |
| Receptacle Color   | Gray   |
| Shipping Dimensions (hwd / in.)                            | 1.50 x 4.25 x 6.50   |
| Shipping Dimensions (hwd / cm)                             | 3.81 x 10.80 x 16.51   |
| Shipping Weight (lbs.)                                     | 0.20   |
| Shipping Weight (kg)                                       | 0.09   |
| Unit Dimensions (hwd / in.)                                | 1.49 x 2.16 x 3.07   |
| Unit Dimensions (hwd / cm)                                 | 3.78 x 5.49 x 7.80   |
| Unit Weight (lbs.)   | .17  |
| Unit Weight (kg)   | 0.08   |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |  |
| Antimicrobial  | No   |
| Rotatable Outlets  | No   |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |  |
| Product Certifications                                     | cUL Listed; UL 1449; UL 497A; UL 1363; UL Listed   |
| Product Compliance   | RoHS   |
| <b>WARRANTY</b>  |  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$10,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>