



HVIC

High Voltage Integrated Circuit
600 Volts/±2 Amperes



Description:

M81702FP is a high voltage Power MOSFET and IGBT module driver for half-bridge applications.

Features:

- Floating Supply Voltage
- Output Current
- Half-Bridge Driver
- SOP-16

Applications:

- HID
- PDP
- MOSFET Driver
- IGBT Driver
- Inverter Module Control

Ordering Information:

M81702FP is a ±2 Ampere, 600 Volt HVIC, High Voltage Integrated Circuit

Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	0.31±0.01	7.8±0.3
B	0.41±0.004	10.1±0.1
C	0.21±0.004	5.3±0.1
D	0.12	2.10
E	0.05	1.27
F	0.02±0.002	0.4±0.05
G	0.004	0.1
H	0.07	1.8
J	0.01±0.004	0.1±0.1

Dimensions	Inches	Millimeters
K	0.05	1.25
L	0.024±0.008	0.6±0.2
M	0.1±0.002	0.2±0.05
N	4°±4°	4°±4°
P	0.03 Max.	0.755 Max.
Q	0.006	0.15
R	0.05 Min.	Min. 1.27
S	0.30	7.62
T	0.029	0.76



Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

M81702FP
HVIC, High Voltage Integrated Circuit
 600 Volts/±2 Amperes


Absolute Maximum Ratings, $T_a = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	M81702FP	Units
High Side Floating Supply Absolute Voltage	V_B	-0.5 ~ 624	Volts
High Side Floating Supply Offset Voltage	V_S	-0.5 ~ 600	Volts
High Side Floating Supply Voltage ($V_{BS} = V_B - V_S$)	V_{BS}	-0.5 ~ 24	Volts
Allowable Offset Supply Voltage Minus Surge ($P_W < 1\mu\text{s}$)	$-V_S$	-5	Volts
High Side Output Voltage	V_{HO}	$V_S - 0.5 \sim V_B + 0.5$	Volts
Low Side Fixed Supply Voltage	V_{CC}	-0.5 ~ 24	Volts
Low Side Output Voltage	V_{LO}	-0.5 ~ $V_{CC} + 0.5$	Volts
Logic Supply Voltage	V_{DD}	-0.5 ~ 24	Volts
Logic Input Voltage (H_{IN}, L_{IN})	V_{IN}	-0.5 ~ $V_{DD} + 0.5$	Volts
Shutdown Input Voltage	S_D	-0.5 ~ $V_{DD} + 0.5$	Volts
Low Side Return Offset Voltage ($V_{CC} - L_{GND} < 24\text{V}$)	L_{GND}	-5 ~ $V_{CC} + 0.5$	Volts
Allowable Offset Supply Voltage Transient	dV_S/dt	±50	V/ns
Package Power Dissipation ($T_a = 25^\circ\text{C}$, On Board)	P_d	0.88	Watts
Linear Derating Factor ($T_a > 25^\circ\text{C}$, On Board)	K_θ	-8.8	mW/°C
Junction to Case Thermal Resistance	$R_{th(j-c)}$	50	°C/W
Junction Temperature	T_j	-20 ~ 125	°C
Operation Temperature	T_{opr}	-20 ~ 75	°C
Storage Temperature	T_{stg}	-40 ~ 125	°C

Recommended Operating Conditions

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
High Side Floating Supply Absolute Voltage	V_B		$V_S + 10$	—	$V_S + 20$	Volts
High Side Floating Supply Offset Voltage	V_S		0	—	500	Volts
High Side Floating Supply Voltage	V_{BS}	$V_{BS} = V_B - V_S$	10	—	20	Volts
Low Side Fixed Supply Voltage	V_{CC}		10	—	20	Volts
Logic Supply Voltage	V_{DD}		5	—	20	Volts
Logic Input Voltage	V_{IN}	H_{IN}, L_{IN}	0	—	V_{DD}	Volts
Shutdown Input Voltage	S_D		0	—	V_{DD}	Volts
Low Side Return Offset Voltage	L_{GND}		-5	—	5	Volts

THERMAL DERATING FACTOR CHARACTERISTICS



M81702FP

HVIC, High Voltage Integrated Circuit

600 Volts/±2 Amperes

Electrical Characteristics

T_a = 25°C, V_{CC} = V_{BS} (= V_B - V_S) = V_{DD} = 15V, L_{GND} = 0V unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Floating Supply Leakage Current	I _{FS}	V _B = V _S = 600V	—	—	1	μA
V _{BS} Standby Current	I _{BS}		—	0.4	0.7	mA
V _{CC} Standby Current	I _{CC}		—	0.75	1.5	mA
V _{DD} Standby Current	I _{DD}		—	—	10	μA
High Level Output Voltage	V _{OH}	I _O = 0A, L _O , H _O	13.8	14.4	—	Volts
Low Level Output Voltage	V _{OL}	I _O = 0A, L _O , H _O	—	—	0.1	Volts
High Level Input Threshold Voltage	V _{IH15}	H _{IN} , L _{IN}	—	8.4	9.5	Volts
Low Level Input Threshold Voltage	V _{IL15}	H _{IN} , L _{IN}	6.0	6.8	—	Volts
High Level Input Threshold Voltage	V _{IH5}	H _{IN} , L _{IN} (V _{DD} = 5V)	—	3.1	4.1	volts
Low Level Input Threshold Voltage	V _{IL5}	H _{IN} , L _{IN} (V _{DD} = 5V)	1.4	2.4	—	Volts
Shutdown High Level Input Threshold Voltage	V _{ISDH15}	S _D	—	8.4	9.5	Volts
Shutdown Low Level Input Threshold Voltage	V _{ISDL15}	S _D	6.0	6.8	—	Volts
Shutdown High Level Input Threshold Voltage	V _{ISDH5}	S _D (V _{DD} = 5V)	—	3.1	4.1	Volts
Shutdown Low Level Input Threshold Voltage	V _{ISDL5}	S _D (V _{DD} = 5V)	1.4	2.4	—	Volts
High Level Input Bias Current	I _{IH}	V _{IN} = 15V	—	75	150	μA
Low Level Input Bias Current	I _{IL}	V _{IN} = 0V	—	—	1.0	μA
V _{BS} Supply UV Reset Voltage	V _{BSuvr}		7.5	8.6	9.7	Volts
V _{BS} Supply UV Hysteresis Voltage	V _{BSuvh}		0.1	0.4	0.7	Volts
V _{BS} Supply UV Filter Time	t _{VBSuv}		—	10	—	μs
V _{CC} Supply UV Reset Voltage	V _{CCuvr}		7.5	8.6	9.7	Volts
V _{CC} Supply UV Hysteresis Voltage	V _{CCuvh}		0.1	0.4	0.7	Volts
V _{CC} Supply UV Filter Time	t _{VCCuv}		—	10	—	μs
Output High Level Short Circuit Pulsed Current	I _{OH}	V _O = 0V, V _{IN} = 15V, P _W < 10μs	—	-2.5	—	Amperes
Output Low Level Short Circuit Pulsed Current	I _{OL}	V _O = 15V, V _{IN} = 0V, P _W < 10μs	—	2.5	—	Amperes
Output High Level ON Resistance	R _{OH}	I _O = -200mA, R _{OH} = (V _{OH} - V _O)/I _O	—	10	13	Ω
Output Low Level ON Resistance	R _{OL}	I _O = 200mA, R _{OL} = V _O /I _O	—	2.5	3	Ω
High Side Turn-On Propagation Delay	t _{dLH(HO)}	C _L = 1000pF between H _O - V _S	—	—	350	ns
High Side Turn-Off Propagation Delay	t _{dHL(HO)}	C _L = 1000pF between H _O - V _S	—	—	330	ns
High Side Turn-On Rise Time	t _{rH}	C _L = 1000pF between H _O - V _S	—	—	60	ns
High Side Turn-Off Fall Time	t _{fH}	C _L = 1000pF between H _O - V _S	—	—	30	ns
Low Side Turn-On Propagation Delay	t _{dLH(LO)}	C _L = 1000pf between L _O - GND	—	—	350	ns
Low Side Turn-Off Propagation Delay	t _{dHL(LO)}	C _L = 1000pf between L _O - GND	—	—	330	ns
Low Side Turn-On Rise Time	t _{rL}	C _L = 1000pf between L _O - GND	—	—	60	ns
Low Side Turn-Off Rise Time	t _{fL}	C _L = 1000pf between L _O - GND	—	—	30	ns
Delay Matching, High Side and Low Side Turn-On	Δt _{dLH}	t _{dLH(HO)} - t _{dLH(LO)}	—	—	30	ns
Delay Matching, High Side and Low Side Turn-Off	Δt _{dHL}	t _{dHL(HO)} - t _{dHL(LO)}	—	—	30	ns
Shutdown Propagation Delay	t _{SD}	C _L = 1000pF between H _O -V _S , C _L = 1000pF between L _O -GND	—	—	350	ns

M81702FP

HVIC, High Voltage Integrated Circuit

600 Volts/±2 Amperes

FUNCTION TABLE (X: H or L)

H _{IN}	L _{IN}	V _{BS} UV	V _{CC} UV	HO	LO	SD	Behavioral State
L	L	H	H	L	L	L	LO = OFF, HO = OFF
L	H	H	H	L	H	L	LO = ON, HO = OFF
H	L	H	H	H	L	L	LO = OFF, HO = ON
H	H	H	H	H	H	L	LO = ON, HO = ON
X	L	L	H	L	L	L	LO = OFF, HO = OFF, V _{BS} UV tripped
X	H	L	H	L	H	L	LO = ON, HO = OFF, V _{BS} UV tripped
L	X	H	L	L	L	L	LO = OFF, HO = OFF, V _{CC} UV tripped
H	X	H	L	L	L	L	LO = OFF, HO = OFF, V _{CC} UV tripped
X	X	H	H	L	L	H	LO = OFF, HO = OFF, SD = ON


Note : "L" state of V_{BS} UV and V_{CC} UV means that UV trip voltage.

TIMING DIAGRAM

1. Input/Output Timing Diagram

When input signal (H_{IN} or L_{IN}) is "H", then output signal (HO or LO) is "H".


Both input signals (H_{IN} and L_{IN}) are "H", then output signal (HO or LO) becomes "H".




2. Shutdown Input Timing Diagram

When shutdown input signal (SD) is "H", then output signals (HO and LO) are "L".

Output signals (HO and LO) keep "L" by shutdown input signal (SD) is "L" until next input signal (H_{IN} or L_{IN}) is "H".



3. V_{CC} (V_{BS}) Supply Under Voltage Lockout Timing Diagram



4. Allowable Supply Voltage Transient

Allowable high side floating supply voltage (V_{BS}) transient or low side fixed supply voltage (V_{CC}) transient are below 50V/μs. In case V_{BS} or V_{CC} are started more than 50V/μs, output signal (HO or LO) may be "H".