

# Monitor - VL FPM 15 - 2913017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



15-in. display shown

## Key commercial data

Packing unit	0
Minimum order quantity	1
GTIN	 4 046356 662260
Custom tariff number	85285100
Country of origin	TAIWAN

## Technical data

### Display data

Display	38.1 cm/15" TFT active
Resolution	1024 x 768 Pixel (XGA)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Touch screen	Resistive industrial touch screen
Colors	16.2 million

### Computer data

Processor	without
Main memory	without
Processor fan	Without fan
Data memory	without
Interfaces	1x DVI-D, 1x VGA, 2x USB
Network	without
Operating systems	No operating system
Slots	without
Power supply unit	24 V DC +/- 20%

### General data

Installation dimension, width	386.6 mm
Installation dimension, height	285 mm

# Monitor - VL FPM 15 - 2913017

## Technical data

### General data

Note regarding installation dimension	Panel cutout
Mounting type	Panel cutout or VESA mount
Weight	4.51 kg

### Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

## Classifications

### eclass

eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301

### etim

ETIM 4.0	EC001413
----------	----------