



Extruded profile for locking base system, length: 2000 mm, lower part, width: 46.5 mm, width of PCB: 42.5 mm, colour: orange, Note: required profile length = PCB length - 4 mm

### Business data

Article number	<u>5675.3</u>
Article name	RS-SP 0 2000 mm OG
GTIN (EAN)	4044211068615
Packaging unit	1
Quantity unit	M
Weight per piece (not including packaging)	213 g
Weight per piece (including packaging)	213 g
Unit of weight	G
Customs number	39162000
Country of origin	DE
Product description	Extruded profile
Colour	Orange

### Technical data

#### Dimensions

Length	2000 mm
Width	46.5 mm
Height	19 mm

#### Materials

Material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-50 °C
Working temperature, max.	60 °C

#### Further technical data

Required profile length = PCB length	-4 mm
Min. PCB thickness	1.3 mm
Max. PCB thickness	1.7 mm
Min. PCB width of upper level	42.5 mm
Max. PCB width of upper level	42.5 mm

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Media

---

### Accessories

#### Mounting screw



Mounting screw for locking base systems RS-SP, for attaching the mounting feet, end plates and covers

Article number	Article name	GTIN (EAN)	Packaging unit
<a href="#">4560.0</a>	BS RS	4044211080686	100 ST

#### End plate



End plate with snap-in mounting foot for locking base system RS-SP 0, colour: orange. Enables profile to be mounted on Mounting rail TS 35 DIN rail, colour: orange

Article number	Article name	GTIN (EAN)	Packaging unit
<a href="#">3133.3</a>	AP 0/TS OG	4044211058388	20 ST



Mounting plate for direct mount to locking base system RS-SP 0. Enables profile to be mounted on mounting plates using M5 screw, colour: orange

Article number	Article name	GTIN (EAN)	Packaging unit
<a href="#">3134.3</a>	AP 0/D OG	4044211058395	20 ST