



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
COM1	/	8I	/	7I	/	6I	/	5I	/	4I	/	3I	/	2I	/	1I	/	COM1	1A	1H	2A	2H	3A	3H	4A	4H	5A	5H	6A	6H	7A	7H	8A	8H	/	
COM2	/	8F	8J	7F	7J	6F	6J	5F	5J	4F	4J	3F	3J	2F	2J	1F	1J	/	1B	1G	2B	2G	3B	3G	4B	4G	5B	5G	6B	6G	7B	7G	8B	8G	COM2	
COM3	/	8E	8K	7E	7K	6E	6K	5E	5K	4E	4K	3E	3K	2E	2K	1E	1K	/	1C	1L	2C	2L	3C	3L	4C	4L	5C	5L	6C	6L	7C	7L	8C	8L	/	
COM4	COM4	8D	8N	7D	7N	6D	6N	5D	5N	4D	4N	3D	3N	2D	2N	1D	1N	/	1DP	1M	2DP	2M	3DP	3M	4DP	4M	5D	5M	6D	6M	7DP	7M	8DP	8M	/	

NOTES:

- |  |                               |
|--|-------------------------------|
| 1. DISPLAY TYPE: TN                    | 5. OPERATING VOLTAGE: 4.7 V   |
| 2. VIEWING DIRECTION: 6:00             | 6. OPERATING TEMP: -30°C~80°C |
| 3. POLARIZER MODE: POSITIVE/REFLECTIVE | 7. STORAGE TEMP: -40°C~80°C   |
| 4. DRIVER METHOD: 1/4 DUTY 1/3 BIAS    | 8. CONNECTOR: PIN             |