

DESCRIPTION

The CENTRAL SEMICONDUCTOR TIP110, TIP115 series types are Complementary Silicon Power Darlington Transistors designed low speed switching and amplifier applications.

<u>MAXIMUM RATINGS</u> $(T_C = 25^{\circ}C)$

	SYMBOL	TIP110 <u>TIP115</u>	TIP111 <u>TIP116</u>	TIP112 <u>TIP117</u>	<u>UNITS</u>
Collector-Base Voltage	VCBO	60	80	100	v
Collector-Emitter Voltage	VCEO	80	80	100	V
Emitter-Base Voltage	V _{EBO}	5.0	5.0	5.0	V
Collector Current	I _C		2.0		А
Collector Current (Peak)	СМ		4.0		А
Base Current	۱ _B		50		mA
Power Dissipation	PD		50		W
Operating and Storage					
Junction Temperature	T _J ,T _{stg}		-65 to +150)	°C
Thermal Resistance	θ _{JC}		2.5		oC/W

<u>ELECTRICAL CHARACTERISTICS</u> ($T_C = 25^{\circ}C$ unless otherwise noted)

		TIP110		111	TIP1		
		<u>TIP115</u>	<u>TIP</u>	116	<u>TIP1</u>	<u>17</u>	
SYMBOL	TEST CONDITIONS	<u>MIN</u> <u>M</u>	<u>AX MIN</u>	<u>MAX</u>	MIN	<u>MAX</u>	<u>UNITS</u>
Сво	V _{CB} =60V	1.	.0	-		-	mA
ICBO	.V _{CB} =80V		-	1.0		-	mA
I _{CBO}	V _{CB} =100V		•	-		1.0	mA
ICEO	V _{CE} =30V	2.	.0	-		-	mA
ICEO	V _{CE} =40V		-	2.0		-	mA
ICEO	V _{CE} = 50V		-	-		2.0	mA
I _{EBO}	V _{BE} = 5.0V	2.	.0	2.0		2.0	mA
BVCEO	I _C = 30mA	60	80		100		V
V _{CE} (SAT)	$I_{C} = 2.0A, I_{B} = 8.0mA$	2.	.5	2.5		2.5	V
V _{BE(ON)}	$V_{CE} = 4.0V, I_{C} = 2.0A$	2.	.8	2.8		2.8	V
h _{FE}	$V_{CE} = 4.0V, I_{C} = 1.0A$	1000	1000		1000		
h _{FE}	$V_{CE} = 4.0V, I_{C} = 2.0A$	500	500		500		
fT	$V_{CE} = 10V, I_{C} = 750mA, f = 1.0MHz$	25	25		25		MHz

<u>ELECTRICAL CHARACTERISTICS</u> ($T_C = 25^{\circ}C$ unless otherwise noted)

		<u>MIN</u>	<u>MAX</u>	<u>UNITS</u>
Cob	V _{CB} =10V, I _E =0, f=0.1MHz			
	TIP110, TIP111, TIP112		100	pF
C _{ob}	V _{CB} =10V, I _E =0, f=0.1MHz			
	TIP115, TIP116, TIP117		200	pF



145 Adams Avenue Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824 www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- · Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

ss your design challenges.

· Custom product packing

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits

Custom bar coding for shipments

Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>





http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01042
Notification Date:	8/15/16
Last Buy Date:	2/15/17
Last Shipment Date	8/15/17

Summary: The TIP110 series of NPN and PNP Darlington power transistors, with the exception of TIP112 and TIP117, is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
TIP110	TIP112
TIP111	TIP112
TIP115	TIP117
TIP116	TIP117

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.