

VIEW ON MATING SIDE

○	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
○	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	-	-	-	-	-	-			

A = 32 STANDARD CONTACTS L = 3
 B = 32 STANDARD CONTACTS L = 3
 C = 32 STANDARD CONTACTS L = 3
 S = 96 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 2

C	G2/O	a1-32
B	G2/O	b1-32
A	G2/O	a1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN: 09/09/03 CHK'd G.L.: 09/09/03 APPR'd L.L.: 09/09/03	QUALITY SYMBOLS MAJOR \blacktriangledown CRITICAL ∇	GENERAL TOLERANCES: (UNLESS SPECIFIED) DIM INCH INCH 4 PLACES $\pm 0.$ \pm 3 PLACES ± 0.05 \pm 2 PLACES ± 0.1 \pm 1 PLACE ± 0.15 \pm		SCALE DESIGN UNITS [] DIM [] INCH [] MM [] INCH	THIRD ANGLE PROJECTION [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH	DIMENSIONS: SHT REV [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH [] DIM INCH	
	DESCRIPTION C	DRAWN BY & DATE S.S. 10/09/1999	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT				
	REV C	CHECKED BY & DATE G.L. 10/09/1999	APPROVED BY & DATE G.L. 10/09/1999	MOLEX INCORPORATED			
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CAD FILENAME SD-85003-0189.S01	MATERIAL NO. 85003-0189	DRAWING NO. SD-85003-0189	SHEET NO. 1 OF 1	SIZE D	