


Insulation Thickness 0.38mm
Overall Diameter 2.1±0.15mm

Copper Conductor
42/0.16mm
Resistance
(20° (Max). 22.4Ω/km)

Jacket Thickness 0.98mm
Overall Diameter 6.4±0.2mm



(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color		Strip	ROJ	Color
40P Black 90±5° A	LT-202(15A 125V) (NEMA5-15P)	1	7±1	23±3	Black	SVT 18AWGX3C 105°C BLACK Length: 1000±20 mm	5/8" (16mm)	2" (50.8mm)	Black
Nickel-Plated	Plug Terminal	1	7±1	23±3	White		5/8" (16mm)	2" (50.8mm)	White
Nickel-Plated	UL Blades	2	7±1	26±3	Green		5/8" (16mm)	2" (50.8mm)	Green
White	(202 Inner Body)	1							

- NOTE :**
1. PLUG : LT-202 AMERICAN TYPE
 2. CONNECTOR : NA
 3. CORD : SVT 18AWGX3C 105°C BLACK 1M
 4. APPROVALS : UL C-UL
 5. Supplier for flexible cord : RHYTHM
 6. Hi-Pot Test:2000v/1min<1mA>

Marking:
RHYTHM: (UL) E88231 SVT 3X18AWG(0.824mm²)
105°C 300V VW-1 CSA LL54496 SVT
3X18AWG(0.824mm²)105°C 300V VW-1
RHYTHM R

Modification History

		DRAWER	Aaron	DATE	20/10/23	P/N	800-1801-2-SVT0-BL-00100-1
		APPROVE		REV.	0	Dr.No.	1091084
			比例			TOL.	±5mm
	DESCRIPTION			DATE			ALL DIMENSIONS IN mm

CnC Tech
Industrial Cable and Connector Technology