

## PP LC 2x M2.5 holes recep. SM, 1.1 seal



Image is for illustration purposes only. Please refer to product description.

Part number	09 57 442 0503 001
Specification	PP LC 2x M2.5 holes recep. SM, 1.1 seal
HARTING eCatalogue	<a href="https://b2b.harting.com/09574420503001">https://b2b.harting.com/09574420503001</a>

### Identification

Category	Connectors
Series	HARTING PushPull (V4)
Identification	LC duplex
Element	Panel feed trough set
Description of the contact	Singlemode
Description of hood/housing	Compact

### Version

Number of contacts	2
Locking type	PushPull

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥200
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant



**Pushing Performance**  
Since 1945

## Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Naphthalene

## Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)
Approvals	DNV GL

## Commercial data

Packaging size	1,000
Net weight	6.62 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140072657
eCl@ss	27440114 Rectangular connector (for field assembly)