



ELESA original design CFT

4 Type

- SH** 2x2 bores for countersunk screws
- EH** 2x2 bores for socket cap screws / hexagon head screws

Metric table

Dimensions in: millimeters - inches

1		2		3		d ₂	h ₁	h ₂	h ₃	h ₄ -0.5	h ₅	l ₃	m ₁ ±0,25	m ₂ ±0,25	A/F Type EH
Nominal dimension	Actual dimension	Nominal dimension	Actual dimension	Type SH	Type EH										
40	38	40	39.5	4.5	4.5	3	13	9	4.5	4	18	17.5	25	25	7
1.57	1.50	1.57	1.56	0.18	0.18	0.12	0.51	0.35	0.18	0.16	0.71	0.69	0.98	0.98	0.28
48	48	49	49.5	5.5	5.5	4	16.5	11.5	5	5	23	21.5	31	30.5	8.5
1.89	1.89	1.93	1.95	0.22	0.22	0.16	0.65	0.45	0.20	0.20	0.91	0.85	1.22	1.20	0.33
48	48	49	49.5	-	6.5*	4	16.5	11.5	5	5	23	21.5	31	30.5	10
1.89	1.89	1.93	1.95		0.26	0.16	0.65	0.45	0.20	0.20	0.91	0.85	1.22	1.20	0.39
65	63	65	65	6.5	6.5	5	21.5	15	7.5	7	30	29	40	40	10
2.56	2.48	2.56	2.56	0.26	0.26	0.20	0.85	0.59	0.30	0.28	1.18	1.14	1.57	1.57	0.39

*Not suitable for socket cap screw DIN 912-M6

Specification

- Body
Plastic
Technopolymer (Polyamide PA)
- Glass fiber reinforced
- Black, matte finish
- Temperature resistant up to 80 °C (175 °F)
- Pin
Plastic
Technopolymer (Polyacetal POM)
- Cover cap
Plastic
Technopolymer (Polyacetal BPT)
Black, shiny finish
- RoHS compliant

Information

The cover of EN 151.3 hinges prevents dirt from settling in the area of the screws. It also gives the hinge an attractive appearance.

see also...

- *List of Hinge Types*
- *Hinges without Indexing Positions EN 122.2 (with Cover Caps)*
- *Adjustable Alignment Hinges GN 238 (Adjustable, with Cover Caps)*

How to order	
1	Width l ₁
2	Length l ₂
3	Bore diameter d ₁
4	Type

1 2 3 4
EN 151.3-48-49-5.5-EH