## 18 INCHES LENGTH





Connector A 132453 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm LMR-240 Continuity/Hi-Pot Connector B 031-6825 TNC Plug Straight Brass Nickel + Heatshrink

## **Assembly & Label Notes**

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A		Cable			Connector B	
Part #:	132453	Part #:	LMR-240	Part #:	031-6825	
Description:	SMA BHD JK LMR240 Optimized 50O	Description:	LMR-240 - FEP 0.24	Description:	TNC PLUG LMR240 LMR240-UF 50O	
Type:	SMA	Dielectric:	FEP	Type:	TNC	
Gender:	Jack	Shielding:	Braid	Gender:	Plug	
Body Type:	Straight	Diameter:	0.24	Body Type:	Straight	
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder	
Polarity:	Standard	Sheathing:	None	Polarity:	Standard	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:	Bulkhead - Rear Mount	Length:	18 Inches	Mounting:	Cable	
Body Material:	Brass			Body Material:	Brass	
Body Finish:	Gold			Body Finish:	Nickel	
IP Rating:	None			IP Rating:	None	
Contact Material:	Beryllium Copper			Contact Material:	Brass	
Contact Finish:	Gold			Contact Finish:	Gold	
Max. Freq.:	6 GHz			Max. Freq.:	6 GHz	
Booting:	SMA Jack Straight BHD			Booting:	TNC Plug Straight	
				Clocking:	0°	



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-JK/TNC-ST-PL LMR24 18I

Part No

Q-32059000M018I

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES