

Key Features



Product Description

The ViewSonic CDE3204 is a great value, high performance 32" (31.5" viewable) Full HD LED commercial display for hotel, restaurant and hospitality environments. In addition to versatile connectivity options, including HDMI, VGA, DVI, SPDIF, YPbPr, the display comes with a simple and convenient USB multimedia playback functionality. With 1920 x 1080 resolution, 350-nit brightness, wide viewing angles and dual 10W stereo speakers, the slim-bezel CDE3204 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one-touch-play, with additional features for multiple connected devices such as HD set-top-boxes, media players, and Blu-ray™ players. An RS232 port with IR pass-through provides automated control for hospitality installation. Creating a more comfortable viewing experience, the display is equipped with Flicker-Free and Blue Light Filter technologies. In addition, free-bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop.

Visit Us ■ www.viewsonic.com

LCD PANEL

Panel Size:	32" (31.5" diagonal)
Type/ Tech:	ADS type
Display Area (mm):	698.4 (H) x 392.85 (V)
Aspect Ratio:	16:09
Resolution:	1920 x 1080
Colors:	16.7 M colors
Brightness:	350 nits (typ.)
Contrast Ratio:	1200:1 (typ.)
Response Time:	8 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	ELED
Backlight Life:	50,000 Hours (typ.)
Hardness:	Hard coating(3H), Anti-glare treatment of the front polarizer (Haze 1%)

INPUT

HDMI:	x 2 (HDMI1.4)
RGB / VGA:	x 1
DVI:	x 1
Audio:	x 1
CVBS:	x 1
YPbPr:	x 1
RS232:	x 1

OUTPUT

Audio:	x 1
SPDIF:	x 1
IR:	x 1

USB

Type A:	x 1
---------	-----

SPEAKERS

10W x 2

COMPATIBILITY

VGA:	480i, 480p,720p,1080i,1080p
DVI:	480i, 480p,720p,1080i,1080p
HDMI:	480i, 480p,720p,1080i,1080p

CONTROLS

Physical- Top OSD:	POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU Picture Mode, Contrast, Brightness, Sharpness, Tint, Color, Blue Light Filter, Color Temp, Zoom Mode, DLC Sound Mode, Digital Output, Surround Sound, AVC, Balance Sleep Timer, Time Zone, DST, Time Format, Clock, Time Management Menu Language, Transparent, OSD Time Out, Restore Default, Software Update(USB), CEC, Blue Screen, Monitor ID, HDMI Mode System Lock, Change Password, Input Block
--------------------	--

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	Normal 41W, Max 68W

ERGONOMICS

Wall Mount (VESA®):	200x4200mm ; Screw: M4*L8
---------------------	---------------------------

OPERATING CONDITIONS

Temperature (° C):	0 to 40°C (Landscape)/0 to 35°C (Portrait)
Humidity:	20% ~ 80% non-condensing

"DIMENSIONS (W X H X D)"

Physical (inch / mm):	733 x 468.5 x 191.4 mm / 28.86 x 18.44 x 7.54 in
Physical w/o Stand (inch / mm):	733 x 431.2 x 57.0 mm / 28.86 x 16.98 x 2.24 in
Packaging (inch / mm):	794 x 496 x138 mm / 31.26 x 19.53 x 5.43 in

WEIGHT

Net (lb / kg):	6.4 kg / 14.11 lbs
Net w/o Stand (lb / kg):	6.3 kg / 13.89 lbs
Gross (lb / kg):	8.07 kg / 17.79 lbs

WHAT'S IN THE BOX?

1. CDE3204 commercial display
2. Remote Control with batteries
3. User manual CD wizard
4. Quick Start Guide
5. Power Cables

CONTACT DETAILS

Gross (lb / kg):	19.8 kg / 43.65 lbs
------------------	---------------------