



-Transmission properties in accordance with ISO/IEC 11801: Class D  
 -Protection level: IP67/65  
 -Temperature range: -25°C ...+70°C

RJ45 Ethernet Trailing Cable  
 AWG22/7, 2x2x0.75, PUR, Cat. 5+

20	21034851440		40
19	21034851425		25
18	21034851420		20
17	21034851415		15
16	21034851412		12
15	21034851411		11
14	21034851410		10
13	21034851409		9
12	21034851408		8
11	21034851457		7.5
10	21034851456		6.5
9	21034851406		6
8	21034851405		5
7	21034851454		3.5
6	21034851403		3
5	21034851453		2.5
4	21034851402		2
3	21034851451		1.5
2	21034851401		1
1	21034851452		0.3
<b>Cont. no.</b>	<b>Part no.</b>	<b>Type of cable</b>	<b>Dim. a[m]</b>

		All rights reserved Department EC PD - RO		All Dimensions in mm Original Size DIN A3		Scale 1.5:1		Free size tol.		Ref. Sub.			
HARTING Electronics GmbH D-32339 Espelkamp		Title <b>M12 D-coded Cable Assembly</b>		Created by TOMUTA		Inspected by AVRAM		Standardisation HOFFMANN		Date 2014-03-11		State Final Release	
Type TB		Number 210348514XX		Doc-Key / ECM-Nr. 100110827/UGD/004/D 50000072635		Rev. D		Page 1/1					