

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



FLIP TOP CRIMP HEAD

3/8" FEMALE PARKER FITTING

CT-920CH/CCP
MULTI-USE (CRIMP, CUT, PUNCH) TOOL



NOTES, UNLESS OTHERWISE SPECIFIED:

The CT-920CH/CCP Hydraulic Multi-Use Tool is designed to crimp, cut and punch:

- Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to www.panduit.com for more information.
- Cuts Aluminum and Copper code conductor cable up to 1.57" [40mm].
- Cuts Aluminum and Mild Steel Threaded Rod; M5 to M12, and 1/4 to 1/2 UNC Thread.
- Punch capacity 5-5/8" (144 mm) diameter round in 10 Gauge (3.42 mm) mild steel using Greenlee punches and Panduit Punch Drive Adapter.

The CT-920CH/CCP Tool includes:

Qty.	Description / Item
1	Hydraulic Multi-Use (Crimp, Cut, Punch) Tool
1	UA12TKL Die Adapter Set
1	Carrying Bag

Technical Information:

Tool Weight	9.75 lbs. (4.42 kg)
Dimensions	13.9" L x 4.5" H x 2.7" W [354 L x 114 H x 69 W] mm
Crimping Force	12 tons (108 kN)

Tools are to be used with Panduit hydraulic pumps, hoses, crimp dies, and accessories (sold separately). Go to www.panduit.com for more information.

Copy of operation manual and accessory information can be found at: www.panduit.com.

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	CT-920CH/CCP				CUSTOMER DRAWING	
							ITEM REVISION NAME:				PANDUIT	
							00084SLP_DC/00				MATERIAL:	
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:				DRAWING NUMBER:	
							(.x) ± --- (.xxx) ± ---				00084SLP_DC	
							(.xx) ± --- ANGLES ± ---				SHT 1 OF 1	
							THIRD ANGLE PROJECTION				SIZE B	
							DRAWN BY:	DATE:	CHK	SCALE		
							BKA	7-21-16	ACC	NONE		