



## Model: USB-16COMi-M

### 16-Port RS-422 485 USB-to-Serial Adapter

The USB-16COMi-M industrial USB to 16-Port RS-422 485 Serial adapter for adding more serial communication devices to your system environment.



## Specifications

Serial Interface	16 x RS-422/485 selectable by DIP switch Connectors 16 x DB9 male
Speed	up to 3000kbps
Available Modes	RS422 full duplex RS485 4-wire, full duplex RS485 2-wire, half duplex, with echo RS485 2-wire, half duplex, without echo
Signals	RS422 TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS- RS485 2 wire Data-, Data+ RS485 4 wire TxD+, TxD-, RxD+, RxD-
USB Interface	USB 2.0
Power	Built-in AC to DC switching power supply, wide Range AC input from 100VAC to 240VAC
Driver	Windows 2000 to Windows 8, Windows Server 2000 to 2008 R2, Both x86 and x64 Editions Linux (Kernel 2.6.3.1 and up built-in support)
Dimensions	429 x 147 x 44 mm ( W x L x H ), 451 x 152 x 44 mm with DB9 connector and ears
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)
Approvals	EN55022 Class B, EN55024, EN61000-3-2, EN61000-3 IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11. CISPR PUB. 22 and FCC Part 15 Class B.

### Features

- Metal case
- Rack mount and DIN-Rail mountable
- RS232/422/485 DB9 male ports
- Speed up to 500/3000 kbps
- Built-in power supply

### Product Information

<b>Product Name:</b>	USB-16COMi-M USB-16COMi-M Adapter, USB cable 0,9m, CD,
<b>Packing List:</b>	English Documentation, DIN-Rail brackets Power cord
<b>Optional Accessories:</b>	N/A