



JKL LAMP PART NO. (REFERENCE)	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms) @ 25°C	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
CF26349-28B	x = .325 y = .295	1715	730	5 ± 1	30,000 ± 3000	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC			DIMENSIONS ARE IN MILLIMETERS		JKL COMPONENTS CORPORATION			
 THIRD ANGLE PROJECTION			TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM			APPV'D BY L.R.		DATE 8/5/09	SIZE A	FSCM NO. 55335	DRAWING NO. CF26349-28B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE		RELEASED DATE 1/29/03	REVISION DATE 8/5/09	REV. NO. A	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	RATED LIFE HRS MINIMUM HEADING & 20,000			RELEASED & CANCEL P-0210-08 & BF26349-28B		
			8/5/09			1/29/03		