

24 INCHES LENGTH



Connector A
132444
SMA Plug Right Angle
Brass Gold + Heatshrink

50 Ohm LMR-195
Continuity/Hi-Pot

Connector B
031-6821
TNC Plug Straight
Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
Part #:	132444	Part #:	LMR-195	Part #:	031-6821
Description:	SMA R/A PLUG LMR195 Optimized 50O	Description:	LMR-195 - FEP 0.195	Description:	TNC PLUG LMR195 LMR195-UF 50O
Type:	SMA	Dielectric:	FEP	Type:	TNC
Gender:	Plug	Shielding:	Braid	Gender:	Plug
Body Type:	Right Angle	Diameter:	0.195	Body Type:	Straight
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Cable	Length:	24 Inches	Mounting:	Cable
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Nickel
IP Rating:	None			IP Rating:	None
Contact Material:	Brass			Contact Material:	Brass
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	6 GHz			Max. Freq.:	6 GHz
Booting:	SMA Plug Right Angle			Booting:	TNC Plug Straight
				Clacking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-RA-PL/TNC-ST-PL LMR19 24I

Part No:
Q-37054000D024I

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES