



Metric table

Dimensions in: millimeters - inches

d ₁	d ₂				d ₃	d ₄	h ₁	h ₂	t	
	Thread								VBA	VBA-FP
25 .98	M 4	M 5	M 6	-	13 .51	7 .28	17 .67	8 .31	9 .35	11 .43
35 1.38	M 6	M 8	M 10	-	18 .71	11 .43	20 .79	8 .31	13 .51	15 .59
45 1.77	M 5*	M 6	M 8	M 10	22 .87	11 .43	26 1.02	12 .47	13 .51	18 .71
55 2.17	M 8	-	-	-	25 .98	13 .51	29 1.14	15 .59	14 .55	18 .71
55 2.17	M 10	-	-	-	25 .98	-	29 1.14	15 .59	15 .59	18 .71
55 2.17	M 12	-	-	-	25 .98	-	29 1.14	15 .59	18 .71	18 .71

*Only available for VBA

Specification

- Eight lobed knob
Nylon plastic
 - Temperature resistant up to 230 °F (110 °C)
 - Glass filled
 - Black, matte finish
- Tapped insert
Brass, molded-in
- RoHS compliant

Information

VBA and VBA-FP are economical but durable eight lobed knobs for many applications.

How to order (Blind tapped insert) 1 2 VBA-45-M5	1	Handle diameter d ₁
	2	Thread d ₂
How to order (Through tapped insert) 1 2 VBA-FP-55-M8	1	Handle diameter d ₁
	2	Thread d ₂