

## LOW NOISE 150mA LDO REGULATOR

NO.EA-149-160426

### OUTLINE

The RP103x Series are CMOS-based voltage regulator ICs with high output voltage accuracy, extremely low supply current, low ON-resistance, and high ripple rejection. Each of these ICs consists of a voltage reference unit, an error amplifier, resistor-net for voltage setting, a current limit circuit, and a chip enable circuit.

These ICs perform with low dropout voltage and a chip enable function. The line transient response and load transient response of the RP103x Series are excellent, thus these ICs are very suitable for the power supply for hand-held communication equipment.

The output voltage of these ICs is fixed with high accuracy. Since the packages for these ICs are DFN(PLP)1010-4, SC-82AB, SC-88A, SOT-23-5, therefore high density mounting of the ICs on boards is possible.

### FEATURES

- Supply Current .....Typ. 36 $\mu$ A
- Standby Mode .....Typ. 0.1 $\mu$ A
- Dropout Voltage.....Typ. 0.21V ( $I_{OUT}=150\text{mA}$ ,  $V_{OUT}=2.8\text{V}$ )
- Ripple Rejection .....Typ. 75dB ( $f=1\text{kHz}$ )
- Temperature-Drift Coefficient of Output Voltage .....Typ.  $\pm 30\text{ppm}/^\circ\text{C}$
- Line Regulation .....Typ. 0.02%/V
- Output Voltage Accuracy ..... $\pm 1.0\%$
- Packages.....DFN(PLP)1010-4, SC-82AB, SC-88A, SOT-23-5
- Input Voltage Range .....1.7V to 5.25V
- Output Voltage Range .....1.2V to 3.3V (0.1V steps)  
(For other voltages, please refer to MARK INFORMATIONS.)
- Built-in Fold Back Protection Circuit.....Typ. 40mA (Current at short mode)
- Ceramic capacitors are recommended to be used with this IC .... 0.47 $\mu$ F or more


### APPLICATIONS

- Power source for portable communication equipment.
- Power source for electrical appliances such as cameras, VCRs and camcorders.
- Power source for battery-powered equipment.
- Power source for home appliances.

## RP103x

NO.EA-149-160426

## BLOCK DIAGRAMS



## SELECTION GUIDE

The output voltage, auto discharge function, package, and the taping type, etc. for the ICs can be selected at the user's request.

| Product Name     | Package        | Quantity per Reel | Pb Free | Halogen Free |
|------------------|----------------|-------------------|---------|--------------|
| RP103Kxx1*-TR    | DFN(PLP)1010-4 | 10,000 pcs        | Yes     | Yes          |
| RP103Qxx1*-TR-FE | SC-82AB        | 3,000 pcs         | Yes     | Yes          |
| RP103Qxx2*-TR-FE | SC-88A         | 3,000 pcs         | Yes     | Yes          |
| RP103Nxx1*-TR-FE | SOT-23-5       | 3,000 pcs         | Yes     | Yes          |


xx: The set output voltage ( $V_{SET}$ ) can be designated in the range from 1.2V to 3.3V in 0.1V steps.

Exception: 1.85V=RP103x18x\*5-xx  
2.85V=RP103x28x\*5-xx

\*: CE pin polarity and auto discharge function at off state are options as follows.

- (B) "H" active, without auto discharge function at off state
- (D) "H" active, with auto discharge function at off state

## PIN CONFIGURATIONS



## PIN DESCRIPTIONS

### • DFN(PLP)1010-4

| Pin No | Symbol    | Pin Description              |
|--------|-----------|------------------------------|
| 1      | $V_{OUT}$ | Output Pin                   |
| 2      | GND       | Ground Pin                   |
| 3      | CE        | Chip Enable Pin ("H" Active) |
| 4      | $V_{DD}$  | Input Pin                    |

\*) The tab on the bottom of the package enhances thermal performance and is electrically connected to GND (substrate level). It is recommended that the tab be connected to the ground plane on the board. If not, the tab can be left open.

### • SC-82AB

| Pin No | Symbol    | Pin Description              |
|--------|-----------|------------------------------|
| 1      | CE        | Chip Enable Pin ("H" Active) |
| 2      | GND       | Ground Pin                   |
| 3      | $V_{OUT}$ | Output Pin                   |
| 4      | $V_{DD}$  | Input Pin                    |

### • SC-88A

| Pin No | Symbol    | Pin Description              |
|--------|-----------|------------------------------|
| 1      | CE        | Chip Enable Pin ("H" Active) |
| 2      | NC        | No Connection                |
| 3      | GND       | Ground Pin                   |
| 4      | $V_{OUT}$ | Output Pin                   |
| 5      | $V_{DD}$  | Input Pin                    |

### • SOT-23-5

| Pin No | Symbol    | Pin Description              |
|--------|-----------|------------------------------|
| 1      | $V_{DD}$  | Input Pin                    |
| 2      | GND       | Ground Pin                   |
| 3      | CE        | Chip Enable Pin ("H" Active) |
| 4      | NC        | No Connection                |
| 5      | $V_{OUT}$ | Output Pin                   |

## RP103x

NO.EA-149-160426

### ABSOLUTE MAXIMUM RATINGS

| Symbol    | Item                                | Rating               | Unit |
|-----------|-------------------------------------|----------------------|------|
| $V_{IN}$  | Input Voltage                       | 6.0                  | V    |
| $V_{CE}$  | Input Voltage (CE Pin)              | 6.0                  | V    |
| $V_{OUT}$ | Output Voltage                      | -0.3 to $V_{IN}+0.3$ | V    |
| $I_{OUT}$ | Output Current                      | 180                  | mA   |
| $P_D$     | Power Dissipation* (DFN(PLP)1010-4) | 400                  | mW   |
|           | Power Dissipation* (SC-82AB)        | 380                  |      |
|           | Power Dissipation* (SC-88A)         | 380                  |      |
|           | Power Dissipation* (SOT-23-5)       | 420                  |      |
| $T_{opt}$ | Operating Temperature Range         | -40 to 85            | °C   |
| $T_{stg}$ | Storage Temperature Range           | -55 to 125           | °C   |

\*) For Power Dissipation, please refer to PACKAGE INFORMATION.

#### ABSOLUTE MAXIMUM RATINGS

Electronic and mechanical stress momentarily exceeded absolute maximum ratings may cause the permanent damages and may degrade the life time and safety for both device and system using the device in the field.

The functional operation at or over these absolute maximum ratings is not assured.

#### RECOMMENDED OPERATING CONDITIONS (ELECTRICAL CHARACTERISTICS)

All of electronic equipment should be designed that the mounted semiconductor devices operate within the recommended operating conditions. The semiconductor devices cannot operate normally over the recommended operating conditions, even if when they are used over such conditions by momentary electronic noise or surge. And the semiconductor devices may receive serious damage when they continue to operate over the recommended operating conditions.

## ELECTRICAL CHARACTERISTICS

### ● RP103xxxxB/D

$V_{IN} = V_{SET} + 1V$  ( $V_{OUT} > 1.5V$ ),  $V_{IN} = 2.5V$  ( $V_{OUT} \leq 1.5V$ ),  $I_{OUT} = 1mA$ ,  $C_{IN} = C_{OUT} = 0.47\mu F$ , unless otherwise noted.

The specifications surrounded by   are guaranteed by Design Engineering at  $-40^{\circ}C \leq T_a \leq 85^{\circ}C$ .

### RP103x Series

(Ta=25°C)

| Symbol                                  | Item  | Conditions  | MIN.  | TYP.     | MAX.   | Unit             |
|---|---|---|---|----------|--|------------------|
| $V_{OUT}$                               | Output Voltage*1                                      | Ta=25°C   | $V_{OUT}$<br>x0.99<br>(-20mV)   |          | $V_{OUT}$<br>x1.01<br>(20mV)   | V                |
|   |   | $-40^{\circ}C \leq T_a \leq 85^{\circ}C$  | <span style="border: 1px solid black; padding: 2px;"><math>V_{OUT}</math><br/>x0.985<br/>(-30mV)</span> |          | <span style="border: 1px solid black; padding: 2px;"><math>V_{OUT}</math><br/>x1.015<br/>(30mV)</span> |                  |
| $I_{OUT}$                               | Output Current  |   | <span style="border: 1px solid black; padding: 2px;">150</span>   |          |  | mA               |
| $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ | Load Regulation                                       | $1mA \leq I_{OUT} \leq 150mA$   |   | 10       | <span style="border: 1px solid black; padding: 2px;">30</span>   | mV               |
| $V_{DIF}$                               | Dropout Voltage                                       | Please see the data table on next page  |   |          |  |                  |
| $I_{SS}$                                | Supply Current  | $I_{OUT} = 0mA$   |   | 36       | <span style="border: 1px solid black; padding: 2px;">50</span>   | $\mu A$          |
| Istandby                                | Supply Current (Standby)                              | $V_{CE} = 0V$   |   | 0.1      | 1.0  | $\mu A$          |
| $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$  | Line Regulation                                       | $V_{SET} + 0.5V \leq V_{IN} \leq 5.0V$  |   | 0.02     | <span style="border: 1px solid black; padding: 2px;">0.10</span>                                       | %/V              |
| RR                                      | Ripple Rejection                                      | f = 1kHz, Ripple 0.2Vp-p<br>$V_{IN} = V_{SET} + 1V$ , $I_{OUT} = 30mA$<br>(In case that $V_{OUT} \leq 2.0V$ , $V_{IN} = 3V$ ) |   | 75       |  | dB               |
| $V_{IN}$                                | Input Voltage*2                                       |   | <span style="border: 1px solid black; padding: 2px;">1.7</span>   |          | <span style="border: 1px solid black; padding: 2px;">5.25</span>                                       | V                |
| $\frac{\Delta V_{OUT}}{\Delta T_a}$     | Output Voltage Temperature Coefficient                | $-40^{\circ}C \leq T_a \leq 85^{\circ}C$  |   | $\pm 30$ |  | ppm/ $^{\circ}C$ |
| $I_{SC}$                                | Short Current Limit                                   | $V_{OUT} = 0V$  |   | 40       |  | mA               |
| $I_{PD}$                                | CE Pull-down Current                                  |   |   | 0.3      |  | $\mu A$          |
| $V_{CEH}$                               | CE Input Voltage "H"                                  |   | <span style="border: 1px solid black; padding: 2px;">1.1</span>   |          |  | V                |
| $V_{CEL}$                               | CE Input Voltage "L"                                  |   |   |          | <span style="border: 1px solid black; padding: 2px;">0.3</span>  | V                |
| en                                      | Output Noise*3  | BW = 10Hz to 100kHz<br>$I_{OUT} = 30mA$   |   | 60       |  | $\mu V_{rms}$    |
| $R_{LOW}$                               | Nch On Resistance for Auto Discharge (D Version Only) | $V_{IN} = 4.0V$ , $V_{CE} = 0V$   |   | 30       |  | $\Omega$         |

All test items listed under *Electrical Characteristics* are done under the pulse load condition ( $T_j \approx T_a = 25^{\circ}C$ ) except for Output Noise, Ripple Rejection, and Output Voltage Temperature Coefficient.

\*1 When  $V_{OUT} \leq 2.0V$ , Output voltage accuracy is  $\pm 20mV$ . (When  $-40^{\circ}C \leq T_a \leq 85^{\circ}C$ , Output voltage accuracy is  $\pm 30mV$ )

\*2 Maximum input voltage is 5.25V. If, for any reason the input voltage exceeds 5.25V, it has to be no more than 5.5V, and total operating time should be within 500 hours.

\*3 Output noise is highly dependent on Set output voltage. Please contact us if this matters.

\*RP103Qxx2 (SC-88A) is the discontinued product. As of April in 2016

---

**RP103x**

---

NO.EA-149-160426


The specifications surrounded by  are guaranteed by Design Engineering at  $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$ .

**Dropout Voltage**

( $T_a=25^{\circ}\text{C}$ )

| Set Output Voltage<br>$V_{\text{SET}}$ (V)         | Dropout Voltage $V_{\text{DIF}}$ (V) |       |              |
|--|--------------------------------------|-------|--------------|
|  | Condition                            | TYP.  | MAX.         |
| $1.2\text{V} \leq V_{\text{SET}} < 1.5\text{V}$    | $I_{\text{OUT}}=150\text{mA}$        | 0.500 | <u>0.620</u> |
| $1.5\text{V} \leq V_{\text{SET}} < 1.7\text{V}$    |                                      | 0.380 | <u>0.470</u> |
| $1.7\text{V} \leq V_{\text{SET}} < 2.0\text{V}$    |                                      | 0.340 | <u>0.420</u> |
| $2.0\text{V} \leq V_{\text{SET}} < 2.5\text{V}$    |                                      | 0.280 | <u>0.360</u> |
| $2.5\text{V} \leq V_{\text{SET}} < 2.8\text{V}$    |                                      | 0.220 | <u>0.300</u> |
| $2.8\text{V} \leq V_{\text{SET}} \leq 3.3\text{V}$ |                                      | 0.210 | <u>0.270</u> |

## TYPICAL APPLICATION



(External Components)

C2 0.47 $\mu$ F MURATA: GRM155B30J474KE18B

## TECHNICAL NOTES

When using the RP103x Series, please consider the following points.

### Phase Compensation

In these ICs, phase compensation is made for securing stable operation even if the load current is varied. For this purpose, use a capacitor C2 with good frequency characteristics and ESR (Equivalent Series Resistance). (Note: If additional ceramic capacitors are connected with parallel to the output pin with an output capacitor for phase compensation, the operation might be unstable. Because of this, test these ICs with as same external components as ones to be used on the PCB.)

### PCB Layout

Make V<sub>DD</sub> and GND lines sufficient. If their impedance is high, noise pickup or unstable operation may result. Connect a capacitor C1 with a capacitance value as much as 0.47 $\mu$ F or more between V<sub>DD</sub> and GND pin, and as close as possible to the pins.

Set external components, especially the output capacitor C2, as close as possible to the ICs, and make wiring as short as possible.

**RP103x**

NO.EA-149-160426

**PACKAGE INFORMATION**

• **Power Dissipation (DFN(PLP)1010-4)**

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:



Measurement Conditions

|                  | <b>Standard Land Pattern</b>                |
|------------------|---|
| Environment      | Mounting on Board (Wind Velocity=0m/s)      |
| Board Material   | Glass Cloth Epoxy Plastic (Double-sided)    |
| Board Dimensions | 40mm x 40mm x 1.6mm                         |
| Copper Ratio     | Topside: Approx. 50%, Backside: Approx. 50% |
| Through-holes    | $\phi$ 0.54mm x 24pcs                       |

Measurement Result

( $T_a=25^\circ\text{C}$ )

|                    | <b>Standard Land Pattern</b>   |
|--------------------|--|
| Power Dissipation  | 400mW ( $T_{jmax}=125^\circ\text{C}$ )<br>500mW ( $T_{jmax}=150^\circ\text{C}$ )                               |
| Thermal Resistance | $\theta_{ja} = (125-25^\circ\text{C})/0.4\text{W} = 250^\circ\text{C/W}$<br>$\theta_{jc} = 67^\circ\text{C/W}$ |



**Measurement Board Pattern**  
○ IC Mount Area (Unit:mm)


The above graph shows the Power Dissipation of the package based on  $T_{jmax}=125^\circ\text{C}$  and  $T_{jmax}=150^\circ\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime.

Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

| <b>Operating Time</b> | <b>Estimated years<br/>(Operating 4 hours/day)</b> |
|-----------------------|--|
| 13,000 hours          | 9 years  |



● Package Dimensions (DFN(PLP)1010-4)




\* The tab on the bottom of the package enhances thermal performance and is electrically connected to GND (substrate level). It is recommended that the tab be connected to the ground plane on the board. If not, the tab can be left open.

● Mark Specification (DFN(PLP)1010-4)

①②: Product Code ... Refer to RP103Kxx1x Series Mark Specification Table.

③④: Lot No. ... Alphanumeric Serial Number



## RP103x

NO.EA-149-160426

### ● RP103KSeries Mark Specification Table (DFN(PLP)1010-4)

#### RP103Kxx1B

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP103K121B  | 7A | 1.2V             |
| RP103K131B  | 7B | 1.3V             |
| RP103K141B  | 7Y | 1.4V             |
| RP103K151B  | 7C | 1.5V             |
| RP103K161B  | 7X | 1.6V             |
| RP103K171B  | 7Z | 1.7V             |
| RP103K181B  | 7D | 1.8V             |
| RP103K191B  | 7F | 1.9V             |
| RP103K201B  | 7G | 2.0V             |
| RP103K211B  | 7T | 2.1V             |
| RP103K221B  | 7W | 2.2V             |
| RP103K231B  | 7S | 2.3V             |
| RP103K241B  | 9A | 2.4V             |
| RP103K251B  | 7H | 2.5V             |
| RP103K261B  | 7J | 2.6V             |
| RP103K271B  | 7K | 2.7V             |
| RP103K281B  | 7L | 2.8V             |
| RP103K291B  | 7N | 2.9V             |
| RP103K301B  | 7P | 3.0V             |
| RP103K311B  | 7Q | 3.1V             |
| RP103K321B  | 7U | 3.2V             |
| RP103K331B  | 7R | 3.3V             |
| RP103K181B5 | 7E | 1.85V            |
| RP103K281B5 | 7M | 2.85V            |

#### RP103Kxx1D

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP103K121D  | 8A | 1.2V             |
| RP103K131D  | 8B | 1.3V             |
| RP103K141D  | 8Y | 1.4V             |
| RP103K151D  | 8C | 1.5V             |
| RP103K161D  | 8X | 1.6V             |
| RP103K171D  | 8Z | 1.7V             |
| RP103K181D  | 8D | 1.8V             |
| RP103K191D  | 8F | 1.9V             |
| RP103K201D  | 8G | 2.0V             |
| RP103K211D  | 8T | 2.1V             |
| RP103K221D  | 8W | 2.2V             |
| RP103K231D  | 8S | 2.3V             |
| RP103K241D  | 0A | 2.4V             |
| RP103K251D  | 8H | 2.5V             |
| RP103K261D  | 8J | 2.6V             |
| RP103K271D  | 8K | 2.7V             |
| RP103K281D  | 8L | 2.8V             |
| RP103K291D  | 8N | 2.9V             |
| RP103K301D  | 8P | 3.0V             |
| RP103K311D  | 8Q | 3.1V             |
| RP103K321D  | 8U | 3.2V             |
| RP103K331D  | 8R | 3.3V             |
| RP103K181D5 | 8E | 1.85V            |
| RP103K281D5 | 8M | 2.85V            |

● **Power Dissipation (SC-82AB)**

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:



Measurement Conditions

|                  | Standard Land Pattern                       |
|------------------|---|
| Environment      | Mounting on Board (Wind Velocity=0m/s)      |
| Board Material   | Glass Cloth Epoxy Plastic (Double-sided)    |
| Board Dimensions | 40mm × 40mm × 1.6mm                         |
| Copper Ratio     | Topside: Approx. 50%, Backside: Approx. 50% |
| Through-hole     | φ0.5mm × 44pcs                              |

Measurement Result

( $T_a=25^{\circ}\text{C}$ )

|                    | Standard Land Pattern  | Free Air                                 |
|--------------------|--|--|
| Power Dissipation  | 380mW ( $T_{jmax}=125^{\circ}\text{C}$ )<br>475mW ( $T_{jmax}=150^{\circ}\text{C}$ ) | 150mW ( $T_{jmax}=125^{\circ}\text{C}$ ) |
| Thermal Resistance | $\theta_{ja}=(125-25^{\circ}\text{C})/0.38\text{W}=263^{\circ}\text{C/W}$            | 667 $^{\circ}\text{C/W}$                 |



Measurement Board Pattern

○ IC Mount Area (Unit : mm)

**Power Dissipation**

The above graph shows the Power Dissipation of the package based on  $T_{jmax}=125^{\circ}\text{C}$  and  $T_{jmax}=150^{\circ}\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime.


Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

| Operating Time | Estimated years<br>(Operating 4 hours/day) |
|----------------|--|
| 13,000 hours   | 9 years                                    |

**RP103x**

NO.EA-149-160426


● **Power Dissipation (SC-82AB)**



● **Mark Specification (SC-82AB)**

①②: Product Code ... Refer to **RP103Qxx1x Series Mark Specification Table.**

③④: Lot No. ... Alphanumeric Serial Number



## ● RP103Qxx1xSeries Mark Specification Table (SC-82AB)

## RP103Qxx1B

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP103Q121B  | G0 | 1.2V             |
| RP103Q131B  | G1 | 1.3V             |
| RP103Q141B  | W2 | 1.4V             |
| RP103Q151B  | G2 | 1.5V             |
| RP103Q161B  | W1 | 1.6V             |
| RP103Q171B  | W3 | 1.7V             |
| RP103Q181B  | G3 | 1.8V             |
| RP103Q191B  | G5 | 1.9V             |
| RP103Q201B  | G6 | 2.0V             |
| RP103Q211B  | H7 | 2.1V             |
| RP103Q221B  | W0 | 2.2V             |
| RP103Q231B  | H6 | 2.3V             |
| RP103Q241B  | W4 | 2.4V             |
| RP103Q251B  | G7 | 2.5V             |
| RP103Q261B  | G8 | 2.6V             |
| RP103Q271B  | G9 | 2.7V             |
| RP103Q281B  | H0 | 2.8V             |
| RP103Q291B  | H2 | 2.9V             |
| RP103Q301B  | H3 | 3.0V             |
| RP103Q311B  | H4 | 3.1V             |
| RP103Q321B  | H8 | 3.2V             |
| RP103Q331B  | H5 | 3.3V             |
| RP103Q181B5 | G4 | 1.85V            |
| RP103Q281B5 | H1 | 2.85V            |

## RP103Qxx1D

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP103Q121D  | J0 | 1.2V             |
| RP103Q131D  | J1 | 1.3V             |
| RP103Q141D  | X2 | 1.4V             |
| RP103Q151D  | J2 | 1.5V             |
| RP103Q161D  | X1 | 1.6V             |
| RP103Q171D  | X3 | 1.7V             |
| RP103Q181D  | J3 | 1.8V             |
| RP103Q191D  | J5 | 1.9V             |
| RP103Q201D  | J6 | 2.0V             |
| RP103Q211D  | K7 | 2.1V             |
| RP103Q221D  | X0 | 2.2V             |
| RP103Q231D  | K6 | 2.3V             |
| RP103Q241D  | X4 | 2.4V             |
| RP103Q251D  | J7 | 2.5V             |
| RP103Q261D  | J8 | 2.6V             |
| RP103Q271D  | J9 | 2.7V             |
| RP103Q281D  | K0 | 2.8V             |
| RP103Q291D  | K2 | 2.9V             |
| RP103Q301D  | K3 | 3.0V             |
| RP103Q311D  | K4 | 3.1V             |
| RP103Q321D  | K8 | 3.2V             |
| RP103Q331D  | K5 | 3.3V             |
| RP103Q181D5 | J4 | 1.85V            |
| RP103Q281D5 | K1 | 2.85V            |

**RP103x**

NO.EA-149-160426

● **Power Dissipation (SC-88A)**

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:



Measurement Conditions

|                  | <b>Standard Land Pattern</b>                |
|------------------|---|
| Environment      | Mounting on Board (Wind Velocity=0m/s)      |
| Board Material   | Glass Cloth Epoxy Plastic (Double-sided)    |
| Board Dimensions | 40mm x 40mm x 1.6mm                         |
| Copper Ratio     | Topside: Approx. 50%, Backside: Approx. 50% |
| Through-hole     | $\phi 0.5\text{mm} \times 44\text{pcs}$     |

Measurement Result

( $T_a=25^\circ\text{C}$ )

|                    | <b>Standard Land Pattern</b>   | <b>Free Air</b>   |
|--------------------|--|---|
| Power Dissipation  | 304mW ( $T_{j\text{max}}=125^\circ\text{C}$ )<br>380mW ( $T_{j\text{max}}=150^\circ\text{C}$ ) | 150mW ( $T_{j\text{max}}=150^\circ\text{C}$ )                         |
| Thermal Resistance | $\theta_{ja}=(125-25^\circ\text{C})/0.38\text{W}=263^\circ\text{C/W}$                          | $\theta_{ja}=(125-25^\circ\text{C})/0.15\text{W}=667^\circ\text{C/W}$ |
|                    | $\theta_{jc}=75^\circ\text{C/W}$   | -   |



**Measurement Board Pattern**


○ IC Mount Area (Unit : mm)

The above graph shows the Power Dissipation of the package based on  $T_{j\text{max}}=125^\circ\text{C}$  and  $T_{j\text{max}}=150^\circ\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime.

Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

| <b>Operating Time</b> | <b>Estimated years<br/>(Operating 4 hours/day)</b> |
|-----------------------|--|
| 13,000 hours          | 9 years  |

• Power Dimensions (SC-88A)




Unit : mm

• Mark Specification (SC-88A)

①②③④: Product Code ... Refer to RP103Qxx2x Series Mark Specification Table.

⑤⑥: Lot No. ... Alphanumeric Serial Number



## RP103x

NO.EA-149-160426

### • RP103Qxx2xSeries Mark Specification Table (SC-88A)

#### RP103Qxx2B

| Part Number | ①②③④ | V <sub>SET</sub> |
|-------------|------|------------------|
| RP103Q122B  | G001 | 1.2V             |
| RP103Q132B  | G002 | 1.3V             |
| RP103Q142B  | G023 | 1.4V             |
| RP103Q152B  | G003 | 1.5V             |
| RP103Q162B  | G022 | 1.6V             |
| RP103Q172B  | G024 | 1.7V             |
| RP103Q182B  | G004 | 1.8V             |
| RP103Q192B  | G006 | 1.9V             |
| RP103Q202B  | G007 | 2.0V             |
| RP103Q212B  | G008 | 2.1V             |
| RP103Q222B  | G021 | 2.2V             |
| RP103Q232B  | G009 | 2.3V             |
| RP103Q242B  | G025 | 2.4V             |
| RP103Q252B  | G010 | 2.5V             |
| RP103Q262B  | G011 | 2.6V             |
| RP103Q272B  | G012 | 2.7V             |
| RP103Q282B  | G013 | 2.8V             |
| RP103Q292B  | G015 | 2.9V             |
| RP103Q302B  | G016 | 3.0V             |
| RP103Q312B  | G017 | 3.1V             |
| RP103Q322B  | G018 | 3.2V             |
| RP103Q332B  | G019 | 3.3V             |
| RP103Q182B5 | G005 | 1.85V            |
| RP103Q282B5 | G014 | 2.85V            |

#### RP103Qxx2D

| Part Number | ①②③④ | V <sub>SET</sub> |
|-------------|------|------------------|
| RP103Q122D  | H001 | 1.2V             |
| RP103Q132D  | H002 | 1.3V             |
| RP103Q142D  | H023 | 1.4V             |
| RP103Q152D  | H003 | 1.5V             |
| RP103Q162D  | H022 | 1.6V             |
| RP103Q172D  | H024 | 1.7V             |
| RP103Q182D  | H004 | 1.8V             |
| RP103Q192D  | H006 | 1.9V             |
| RP103Q202D  | H007 | 2.0V             |
| RP103Q212D  | H008 | 2.1V             |
| RP103Q222D  | H021 | 2.2V             |
| RP103Q232D  | H009 | 2.3V             |
| RP103Q242D  | H025 | 2.4V             |
| RP103Q252D  | H010 | 2.5V             |
| RP103Q262D  | H011 | 2.6V             |
| RP103Q272D  | H012 | 2.7V             |
| RP103Q282D  | H013 | 2.8V             |
| RP103Q292D  | H015 | 2.9V             |
| RP103Q302D  | H016 | 3.0V             |
| RP103Q312D  | H017 | 3.1V             |
| RP103Q322D  | H018 | 3.2V             |
| RP103Q332D  | H019 | 3.3V             |
| RP103Q182D5 | H005 | 1.85V            |
| RP103Q282D5 | H014 | 2.85V            |



● **Power Dissipation (SOT-23-5)**

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below. (Power Dissipation (SOT-23-5) is substitution of SOT-23-6.)


Measurement Conditions

|                  | Standard Land Pattern                       |
|------------------|---|
| Environment      | Mounting on Board (Wind Velocity=0m/s)      |
| Board Material   | Glass Cloth Epoxy Plastic (Double-sided)    |
| Board Dimensions | 40mm x 40mm x 1.6mm                         |
| Copper Ratio     | Topside: Approx. 50%, Backside: Approx. 50% |
| Through-holes    | $\phi$ 0.5mm x 44pcs                        |


Measurement Result

( $T_a=25^\circ\text{C}$ )

|                    | Standard Land Pattern  | Free Air                                |
|--------------------|--|---|
| Power Dissipation  | 420mW ( $T_{j\max}=125^\circ\text{C}$ )<br>525mW ( $T_{j\max}=150^\circ\text{C}$ ) | 250mW ( $T_{j\max}=125^\circ\text{C}$ ) |
| Thermal Resistance | $\theta_{ja} = (125-25^\circ\text{C})/0.42\text{W} = 238^\circ\text{C/W}$          | 400 $^\circ\text{C/W}$                  |



Power Dissipation



Measurement Board Pattern

○ IC Mount Area (Unit: mm)

The above graph shows the Power Dissipation of the package based on  $T_{j\max}=125^\circ\text{C}$  and  $T_{j\max}=150^\circ\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime.


Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

| Operating Time | Estimated years<br>(Operating 4 hours/day) |
|----------------|--|
| 9,000 hours    | 6 years                                    |

**RP103x**

NO.EA-149-160426


● **Power Dimensions (SOT-23-5)**



● **Mark Specification (SOT-23-5)**

①②③: Product Code ... Refer to **RP103Nxx1x Series Mark Specification Table.**

④⑤: Lot No. ... Alphanumeric Serial Number




● **RP103Nxx1xSeries Mark Specification Table (SOT-23-5)**

| <b>RP103Nxx1B</b> |     |                  | <b>RP103Nxx1D</b> |     |                  |
|-------------------|-----|------------------|-------------------|-----|------------------|
| Part Number       | ①②③ | V <sub>SET</sub> | Part Number       | ①②③ | V <sub>SET</sub> |
| RP103N121B        | 80A | 1.2V             | RP103N121D        | 81A | 1.2V             |
| RP103N131B        | 80B | 1.3V             | RP103N131D        | 81B | 1.3V             |
| RP103N141B        | 80Y | 1.4V             | RP103N141D        | 81Y | 1.4V             |
| RP103N151B        | 80C | 1.5V             | RP103N151D        | 81C | 1.5V             |
| RP103N161B        | 80X | 1.6V             | RP103N161D        | 81X | 1.6V             |
| RP103N171B        | 80Z | 1.7V             | RP103N171D        | 81Z | 1.7V             |
| RP103N181B        | 80D | 1.8V             | RP103N181D        | 81D | 1.8V             |
| RP103N191B        | 80F | 1.9V             | RP103N191D        | 81F | 1.9V             |
| RP103N201B        | 80G | 2.0V             | RP103N201D        | 81G | 2.0V             |
| RP103N211B        | 80T | 2.1V             | RP103N211D        | 81T | 2.1V             |
| RP103N221B        | 80W | 2.2V             | RP103N221D        | 81W | 2.2V             |
| RP103N231B        | 80S | 2.3V             | RP103N231D        | 81S | 2.3V             |
| RP103N241B        | 82A | 2.4V             | RP103N241D        | 83A | 2.4V             |
| RP103N251B        | 80H | 2.5V             | RP103N251D        | 81H | 2.5V             |
| RP103N261B        | 80J | 2.6V             | RP103N261D        | 81J | 2.6V             |
| RP103N271B        | 80K | 2.7V             | RP103N271D        | 81K | 2.7V             |
| RP103N281B        | 80L | 2.8V             | RP103N281D        | 81L | 2.8V             |
| RP103N291B        | 80N | 2.9V             | RP103N291D        | 81N | 2.9V             |
| RP103N301B        | 80P | 3.0V             | RP103N301D        | 81P | 3.0V             |
| RP103N311B        | 80Q | 3.1V             | RP103N311D        | 81Q | 3.1V             |
| RP103N321B        | 80U | 3.2V             | RP103N321D        | 81U | 3.2V             |
| RP103N331B        | 80R | 3.3V             | RP103N331D        | 81R | 3.3V             |
| RP103N181B5       | 80E | 1.85V            | RP103N181D5       | 81E | 1.85V            |
| RP103N281B5       | 80M | 2.85V            | RP103N281D5       | 81M | 2.85V            |


**RP103x**

NO.EA-149-160426


**TEST CIRCUITS**




**Basic Test Circuit**



**Test Circuit for Supply Current**






**Test Circuit for Ripple Rejection**





**Test Circuit for Load Transient Response**

## TYPICAL CHARACTERISTICS

### 1) Output Voltage vs. Output Current ( $C1=0.47\mu\text{F}$ , $C2=0.47\mu\text{F}$ , $T_a=25^\circ\text{C}$ )




### 2) Output Voltage vs. Input Voltage ( $C1=0.47\mu\text{F}$ , $C2=0.47\mu\text{F}$ , $T_a=25^\circ\text{C}$ )






## RP103x




NO.EA-149-160426





### 3) Supply Current vs. Input Voltage ( $C1=0.47\mu F$ , $C2=0.47\mu F$ , $T_a=25^\circ C$ )



**4) Output Voltage vs. Temperature (C1=0.47μF, C2=0.47μF, I<sub>OUT</sub>=1mA)**




**5) Supply Current vs. Temperature (C1=0.47μF, C2=0.47μF, I<sub>OUT</sub>=0mA)**






**RP103x**

NO.EA-149-160426




**6) Dropout Voltage vs. Output Current ( $C1=0.47\mu F$ ,  $C2=0.47\mu F$ )**









7) Dropout Voltage vs. Set Output Voltage (C1=0.47μF, C2=0.47μF, Ta=25°C)



8) Ripple Rejection vs. Input Bias Voltage (C1=0.47μF, C2=0.47μF, Ripple=0.2V<sub>P-P</sub>, Ta=25°C)




9) Ripple Rejection vs. Frequency (C1=none, C2=0.47μF, Ripple=0.2V<sub>P-P</sub>)



**RP103x**


NO.EA-149-160426

**RP103x33xx**




**10) Input Transient Response ( $I_{OUT}=30mA$ ,  $t_r=t_f=5\mu s$ ,  $T_a=25^\circ C$ )**


**RP103x12xx**









**RP103x25xx**



**RP103x33xx**









**11) Load Transient Response (C1=0.47μF, C2=0.47μF, Ta=25°C)**






**RP103x**



NO.EA-149-160426

**12) Turn On Speed with CE pin (C1=0.47μF, C2=0.47μF, Ta=25°C)**












**13) Turn Off Speed with CE pin (D Version) (C1=0.47µF, C2=0.47µF, Ta=25°C)**







**RP103x**

NO.EA-149-160426





**14) Dropout Voltage vs. Temperature ( $C1=0.47\mu F$ ,  $C2=0.47\mu F$ )**



## RP103x

NO.EA-149-160426



### ESR vs. Output Current

Ceramic type output capacitor is recommended for this series; however, the other output capacitors with low ESR also can be used. The relations between  $I_{OUT}$  (Output Current) and ESR of an output capacitor are shown below. The conditions when the white noise level is under  $40\mu\text{V}$  (Avg.) are marked as the hatched area in the graph.

#### Measurement conditions

Frequency Band : 10Hz to 2MHz

Temperature :  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$







1. The products and the product specifications described in this document are subject to change or discontinuation of production without notice for reasons such as improvement. Therefore, before deciding to use the products, please refer to our sales representatives for the latest information thereon.
2. The materials in this document may not be copied or otherwise reproduced in whole or in part without prior written consent of our company.
3. Please be sure to take any necessary formalities under relevant laws or regulations before exporting or otherwise taking out of your country the products or the technical information described herein.
4. The technical information described in this document shows typical characteristics of and example application circuits for the products. The release of such information is not to be construed as a warranty of or a grant of license under our company's or any third party's intellectual property rights or any other rights.
5. The products listed in this document are intended and designed for use as general electronic components in standard applications (office equipment, telecommunication equipment, measuring instruments, consumer electronic products, amusement equipment etc.). Those customers intending to use a product in an application requiring extreme quality and reliability, for example, in a highly specific application where the failure or misoperation of the product could result in human injury or death (aircraft, spacevehicle, nuclear reactor control system, traffic control system, automotive and transportation equipment, combustion equipment, safety devices, life support system etc.) should first contact us.
6. We are making our continuous effort to improve the quality and reliability of our products, but semiconductor products are likely to fail with certain probability. In order to prevent any injury to persons or damages to property resulting from such failure, customers should be careful enough to incorporate safety measures in their design, such as redundancy feature, fire containment feature and fail-safe feature. We do not assume any liability or responsibility for any loss or damage arising from misuse or inappropriate use of the products.
7. Anti-radiation design is not implemented in the products described in this document.
8. The X-ray exposure can influence functions and characteristics of the products. Confirm the product functions and characteristics in the evaluation stage.
9. WLCSP products should be used in light shielded environments. The light exposure can influence functions and characteristics of the products under operation or storage.
10. There can be variation in the marking when different AOI (Automated Optical Inspection) equipment is used. In the case of recognizing the marking characteristic with AOI, please contact our sales or our distributor before attempting to use AOI.
11. Please contact our sales representatives should you have any questions or comments concerning the products or the technical information.



**Nisshinbo Micro Devices Inc.**

**Official website**

<https://www.nisshinbo-microdevices.co.jp/en/>

**Purchase information**

<https://www.nisshinbo-microdevices.co.jp/en/buy/>

