


**PROPRIETARY INFORMATION:**  
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION		DATE	APPROVED
REV	DESCRIPTION		
A	INITIAL RELEASE, RFS. 16038, JN	04/20/09	BS
B	REVISE RATING, RFS. 16155, JN	05/04/09	BS



**GENERAL SPECIFICATIONS:**

RATING: 15A / 125V AC  
 CABLE TYPE / SIZE: SJT AWG 14 X 3C  
 TEMPERATURE RATING: 60° C MIN.  
 CONDUCTOR COLORS: BLACK / WHITE / GREEN  
 CABLE JACKET COLOR: BLACK  
 LENGTH (L1): 990 ± 30mm  
 LENGTH (L2): 330 ± 15 mm  
 CABLE OUTER DIAMETER: 9.3 ± 0.15 mm  
 END 'A': NEMA 5-15P  
 END 'B' (2): IEC 320 / C13  
 APPROVALS PLUG: UL, CSA or cUL  
 APPROVALS CABLE: UL, CSA or cUL  
 APPROVALS CONNECTOR: UL, CSA or cUL

**NOTES:**

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



**PACKING:**  
 BULK



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
<b>TABULATION BLOCK</b>				
		<b>TOLERANCES:</b> DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		<b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
		<b>MILLIMETERS ANGULAR</b> .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY: JN	DATE: 04/20/09	<b>DWG TITLE: DETACHABLE JUMPER CORDSET</b>		
DRAWN: NF	DATE: 04/20/09	FSCN No.: G, CC	SIZE: A	REV. B
APRVD: HM	DATE: 04/20/09	SCALE: NONE	PART NO: 3011043F701X2(R)	SHEET 1/1

**Foot Note:**  
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

**Limitation of Use:**  
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice