

0.75 METER LENGTH




Connector A
031-6332
BNC Jack Straight
Bulkhead - Rear Mount Brass Nickel IP67

50 Ohm RG-316DB
Continuity/Hi-Pot

Connector B
252119
MCX Plug Right Angle
Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.



Connector A		Cable		Connector B	
Part #:	031-6332	Part #:	RG-316DS	Part #:	252119
Description:	BNC Clamp BHD JK RD-316 IP67 500	Description:	RG-316DB - ST 0.102	Description:	MCX R/A PLUG RG316DB 500
Type:	BNC	Dielectric:	ST	Type:	MCX
Gender:	Jack	Shielding:	Double Braid	Gender:	Plug
Body Type:	Straight	Diameter:	0.102	Body Type:	Right Angle
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount	Length:	0.75 Meter	Mounting:	Cable
Body Material:	Brass			Body Material:	Brass
Body Finish:	Nickel			Body Finish:	Gold
IP Rating:	IP67			IP Rating:	None
Contact Material:	Beryllium Copper			Contact Material:	Brass
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	2 GHz			Max. Freq.:	6 GHz
Booting:	BNC Jack Straight BHD			Booting:	MCX Plug Right Angle
				Clocking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
BNC-ST-JK/MCX-RA-PL G316D 0.75M

Part No:
Q-07017000R.75M

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES