



ANTENNA TECHNOLOGIES LIMITED COMPANY

# Model PA2430TSETM12I Thin Patch Antenna

## Key Features

- Adhesive backing, easy to install
- Thin, small and light-weight for any application
- Solid material for robust applications
- A variety of connectors and pigtail lengths available



Electrical Specifications	PA2430TSETM12I
Frequency Range MHz	2430 Mhz
Gain dBi	4 nominal
VSWR	2.0:1
Front to Back Ratio	14dB
3dB Beamwidth E/H Planes	100/70
Max Power	10 Watts
Cable/length	Pigtail RG316
Connector	TNC Male
Polarization	Vertical

Mechanical Specifications	PA2430TSETM12I
Dimensions	2.0x3.1x0.13
Material	G-10
Mounting	Adhesive Gasket
<b>ENVIRONMENTAL</b>	10-10K FT
Vibration	Ground Transportation
Humidity	0-95% non-condensing
Operating Temp	-40 to +65 C
Storage Temp	-40 to +65 C

22560 Glenn Drive #114 | Sterling, Virginia 20164  
[www.atcllc.com](http://www.atcllc.com) [sales@atcllc.com](mailto:sales@atcllc.com)  
 Office: 703-450-5517

ATLC products for military use may be subject to U.S. ITAR EXPORT CONTROLS, an export license may be required.