




ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE2372 MOSFET P-Ch, Enhancement Mode High Speed Switch TO220 Type Package

Features:

- Dynamic dv/dt Rating
- Fast Switching
- Ease of Paralleling
- Simple Drive Requirements
- TO220 Case Style



Absolute Maximum Ratings:

Continuous Drain Current ($V_{GS} = 10V$), I_D	
$T_C = +25^\circ C$	3.5A
$T_C = +100^\circ C$	2.0A
Pulsed Drain Current (Note 1), I_{DM}	14A
Power Dissipation ($T_C = +25^\circ C$), P_D	40W
Derate Linearly Above $25^\circ C$	0.32W/ $^\circ C$
Gate-to-Source Voltage, V_{GS}	± 20
Inductive Current, Clamp, I_{LM}	14A
Peak Diode Recovery dv/dt (Note 2), dv/dt	5.0V/ns
Operating Junction Temperature Range, T_J	-55° to $+150^\circ C$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ C$
Lead Temperature (During Soldering, 1.6mm from case for 10sec), T_L	$+300^\circ C$
Mounting Torque (6-32 or M3 Screw)	10 lbf•in (1.1N•m)
Thermal Resistance, Junction-to-Case, R_{thJC}	$3.1^\circ C/W$
Thermal Resistance, Junction-to-Ambient, R_{thJA}	$62^\circ C/W$
Typical Thermal Resistance, Case-to-Sink (Flat, Greased Surface), R_{thCS}	$0.5^\circ C/W$

Note 1. Repetitive rating; pulse width limited by maximum junction temperature.

Note 2. $I_{SD} \leq 3.5A$, $di/dt \leq 95A/\mu s$, $V_{DD} \leq V_{(BR)DSS}$, $T_J \leq +150^\circ C$

Note 3. Pules Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

Electrical Characteristics: ($T_J = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	200	-	-	V
Breakdown Voltage Temp. Coefficient	$\frac{V_{(BR)DSS}}{T_J}$	Reference to $+25^\circ\text{C}$, $I_D = 1\text{mA}$	-	0.22	-	$V/^\circ\text{C}$
Static Drain-to-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 1.5A$, Note 3	-	-	1.5	\pm
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	-	4.0	V
Forward Transconductance	g_{fs}	$V_{DS} = 50V, I_D = 1.5A$, Note 3	1.0	-	-	mhos
Drain-to-Source Leakage Current	I_{DSS}	$V_{DS} = 200V, V_{GS} = 0V$	-	-	100	$\leq A$
		$V_{DS} = 160V, V_{GS} = 0V, T_J = +125^\circ\text{C}$	-	-	500	$\leq A$
Gate-to-Source Forward Leakage	I_{GSS}	$V_{GS} = -20V$	-	-	-100	nA
Gate-to-Source Reverse Leakage	I_{GSS}	$V_{GS} = 20V$	-	-	100	nA
Total Gate Charge	Q_g	$I_D = 4A, V_{DS} = 160V, V_{GS} = 10V$, Note 3	-	-	22	nC
Gate-to-Source Charge	Q_{gs}		-	-	12	nC
Gate-to-Drain ("Miller") Charge	Q_{gd}		-	-	10	nC
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 100V, I_D = 1.5A, R_G = 50\pm, R_D = 67\pm$, Note 3	-	15	-	ns
Rise Time	t_r		-	25	-	ns
Turn-Off Delay Time	$t_{d(off)}$		-	20	-	ns
Fall Time	t_f		-	15	-	ns
Internal Drain Inductance	L_D	Between lead, .250in. (6.0) mm from package and center of die contact	-	4.5	-	nH
Internal Source Inductance	L_S		-	7.5	-	nH
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 25V, f = 1\text{MHz}$	-	350	-	pF
Output Capacitance	C_{oss}		-	100	-	pF
Reverse Transfer Capacitance	C_{riss}		-	30	-	pF

Source-Drain Ratings and Characteristics:

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Continuous Source Current (Body Diode)	I_S		-	-	3.5	A
Pulsed Source Current (Body Diode)	I_{SM}	Note 1	-	-	14	A
Diode Forward Voltage	V_{SD}	$T_J = +25^\circ\text{C}, I_S = 3.5A, V_{GS} = 0V$, Note 3	-	-	7.0	V
Reverse Recovery Time	t_{rr}	$T_J = +25^\circ\text{C}, I_F = 3.5A$, $di/dt = 100A/\mu s$, Note 3	-	300	450	ns
Reverse Recovery Charge	Q_{rr}		-	1.9	2.9	$\leq C$
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by $L_S + L_D$)				

Note 1. Repetitive rating; pulse width limited by maximum junction temperature.

Note 3. Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$.

