Data sheet 27154.5 PQI 6/4 BU



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 29.8 mm, Colour: Blue

RAL: Ähnlich 5005

Business data

Article number	<u>27154.5</u>
Article name	PQI 6/4 BU
GTIN (EAN)	4044211234348
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	5.99 g
Weight per piece (including packaging)	6.14 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27154.9
Product description	Insulated cross-connector

Data sheet





Technical data	
Dimensions	
Length	4 mm
Width	29.8 mm
Height	22.5 mm
Pitch size	8.1 mm
Ratings	
Max. voltage	800 V
Rated current	41 A
Current load, max.	41 A
Rated cross-section	6 mm²
Contamination degree	3
Connection data	
No. of poles	4
Materials	
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Further technical data	
Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	4
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet 27154.5 PQI 6/4 BU



Media

Data sheet

27154.5 PQI 6/4 BU



Accessories

##INVERSE##CONTA-CONNECT



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27021.2	PSL 6/3A GNYE	4044211223960	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27023.2	PSL 6/4A GNYE	4044211224004	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27019.2	PSL 6/2A GNYE	4044211223922	50 ST