



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

SDS Number: 113  
 Revision Date: 04/03/2015  
 Supersedes Date: 01/28/2013

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: WATER REMOVABLE SOLDERING PASTE**

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Type: Solder Flux  
 Product Name: **WATER REMOVABLE  
 SOLDERING PASTE**  
 Part Number(s): **10-202**

Emergency Contact: **Chemtrec**  
 Phone: **(800) 424-9300**

**SECTION 2: HAZARD IDENTIFICATION**

**GHS Classification:**

Acute Tox. 4 \*  
 Skin Corr. 1B  
 Aquatic Acute 1  
 Aquatic Chronic 1  
 Repro 2  
 Eye Irrit. 2



**GHS Label Elements:**

**CITRIC ACID & NONYLPHENOL  
 DANGER**

**H Codes:** H302, H314, H319, H410, H335, H361fd  
 Harmful if swallowed  
 May cause respiratory irritation  
 May be harmful in contact with skin  
 Suspected of damaging fertility  
 Toxic to aquatic life with long lasting effects

**P Codes:**

P264, 270, 280, 301+312, 330, 501, 260, 301+330+331, 303+361+353+310, 363, 304+340, 321, 405, 273, 305+351+338+310, 337+313, 302+352, 308+313, 201, 202, 281, 391  
 Avoid breathing dust/mist/vapors/fumes/spray. Do not get in eyes, on skin, or on clothing. Use in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not breathe dust/fume/gas/mist/vapor/spray. Do not eat, drink or smoke when using this product. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. IF INHALED: Remove victim to to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor. Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed compatible container in cool dry place. Avoid release to the environment. Dispose of contents/container in accordance with specified local/regional/national/international regulations for disposal. Keep out of the reach of children. Read label and SDS prior to use.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 113  
Revision Date: 04/03/2015  
Supersedes Date: 01/28/2013

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: WATER REMOVABLE SOLDERING PAST

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS #	OSHA TWA	ACIGH TWA	Other limits	%
Nonylphenol	9016-45-9	NE	NE	NE	

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.  
An ingredient marked with an asterisk(\*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

#### SECTION 4: FIRST AID MEASURES

**Signs and symptoms of exposure:** Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

**Medical conditions aggravated by exposure:** Skin, kidney and respiratory conditions.

**Emergency first aid procedures:**

Skin: Flush with water immediately - Seek medical attention if necessary

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical attention. Never give anything by mouth to an unconscious person

Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention

#### SECTION 5: FIRE FIGHTING MEASURES

**Extinguishing media:** dry chemical.

**Special fire fighting procedures:** use self sustaining respiratory suit.

**Unusual Fire and Explosion Hazards:** May release hydrochloric acid, chlorine, hydrocarbons.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Methods and materials:** Flush into chemical sewer or soak up with a suitable absorbent. Wear adequate protection as described in section 8.

**Environmental Precautions:** Avoid release to the environment. Collect spillage.

#### SECTION 7: HANDLING & STORAGE

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 113  
Revision Date: 04/03/2015  
Supersedes Date: 01/28/2013

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: WATER REMOVABLE SOLDERING PAST**

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limit Values:** See section 3.  
Respiratory Protection (type): Organic vapor/Acid mask required for fumes above TWA.  
Ventilation: Local Exhaust preferred Special: NE  
Mechanical: OK Other: NE  
Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield  
Other Protective Clothing or Equipment: as required to avoid contact.  
Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 500 F Specific Gravity: 1.10  
Vapor Pressure (mm Hg): NE Melting Point: NE  
Vapor Density: NE Evaporation Rate: <1 (butyl acetate=1)  
Solubility in water: near 100% pH: NE  
Flash Point: 400 F (TOC) Flammable Limits: lcl: NE uel: NE  
Appearance and odor: White paste, odorless.

### SECTION 10: STABILITY AND REACTIVITY

**Stability :** STABLE Conditions to avoid : none

**Incompatibility (materials to avoid):** strong bases & acids, oxidizers, sulfides, halogens.  
**Hazardous Decomposition or Byproducts (incomplete combustion):** Hydrochloric acid, chlorine, hydrocarbons.  
**Hazardous Polymerization:** WILL NOT OCCUR Conditions to avoid: none

### SECTION 11: TOXICOLOGICAL INFORMATION

**Routes of entry:** Inhalation: yes Skin: yes Ingestion: yes

**Health Hazards (acute and chronic):** Transient skin, eye and respiratory tract irritation may occur with fume or product contact. Inhalation may result in transient irritation. Ingestion toxicity is low, LD50 (rat) > 500 mg/kg. Ingestion of very large amounts may result in gastric discomfort. Chronic hazards associated with gross over exposure include respiratory inflammation from inhalation, and gastro intestinal, liver, kidney effects from ingestion. Studies show that health risks vary by individual. Minimize exposure as a precaution.

**Carcinogenicity:** not determined NPT? no IARC Monographs? no

### SECTION 12: ECOLOGICAL INFORMATION

**Toxicity:** NE **Persistence & Degradability:** NE  
**Bio-accumulative Potential:** NE **Mobility in Soil:** NE  
**PBT & vPvB Assessment:** NE **Other Adverse Effects:** NE



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 113  
Revision Date: 04/03/2015  
Supersedes Date: 01/28/2013

## MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: WATER REMOVABLE SOLDERING PAST

#### SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** dispose of in accordance with all local state and federal regulations

**Other Precautions:** Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

#### SECTION 14: TRANSPORT INFORMATION

**DOT Classification:** Non-Hazardous  
**Marine Pollutant:** NE

#### SECTION 15: REGULATORY INFORMATION

NFPA Classification (NFPA 325M, 8<sup>th</sup> edition)(Health, Flammability, Reactivity): 1-1-0  
This product contains components known to the state of California to cause cancer or reproductive harm.

#### SECTION 16: OTHER INFORMATION

NE = not established NA = not applicable

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.