



**SS** Stainless Steel

**2** Type

**D** Consisting of three parts

**Metric table**

**1**

Dimensions in: millimeters - inches

s Square	b	d <sub>1</sub> Thread	d <sub>2</sub> Pin	h	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub> max.	m
12 0.47	15 0.59	M 6	6 0.24	39.2 1.54	10 0.39	5 0.20	14 0.55	9 0.35	27.2 1.07
16 0.63	20 0.79	M 8	8 0.31	49 1.93	14 0.55	8 0.31	22 0.87	16 0.63	33 1.30

**Specification**

**3**

- Body, pin, washer
  - Stainless steel AISI 303 **NI**
  - Stainless steel AISI 316 **A4**
- Hexagon nut ISO 4032  
Stainless steel AISI 304
- Serrated washer DIN 6797  
Stainless steel AISI 304
- [Stainless Steel Characteristics](#) → page QVX
- [RoHS compliant](#)

**Information**

GN 129.5 stainless steel hinges are used for doors which are flush with the frame on the outside. They are especially suitable for tamper-proof doors and flaps. When mounted inside, the hinges are not removable from the outside and therefore protect against manipulation.

see also...

- [List of Hinge Types](#) → page QVX
- [Hinges GN 129.2](#) → page QVX

How to order <b>GN 129.5-16-D-A4</b>	<b>1</b> Square s
	<b>2</b> Type
	<b>3</b> Material

3.1  
3.2  
3.3  
3.4  
3.5  
3.6  
3.7  
3.8  
3.9  
3.10