

product type designation



M876-4 LTE (NAM)

SCALANCE M876-4 LTE (4G) NAM; for wireless IP communication from Ethernet-based automation devices via LTE (4G) mobile radio, optimized for usage in North America, VPN, Firewall, NAT; 4-port switch; 2x SMA antennas, MIMO Technology; 1x digital input, 1x digital output; observe national approvals.

transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
transfer rate	
<ul style="list-style-type: none"> for GPRS transmission / with downlink / maximum 	85.6 kbit/s
<ul style="list-style-type: none"> for GPRS transmission / with uplink / maximum 	85.6 kbit/s
<ul style="list-style-type: none"> with eGPRS transmission / with downlink / maximum 	236.8 kbit/s
<ul style="list-style-type: none"> with eGPRS transmission / with uplink / maximum 	236.8 kbit/s
<ul style="list-style-type: none"> with UMTS transmission / with downlink / maximum 	14.4 Mbit/s
<ul style="list-style-type: none"> with UMTS transmission / with uplink / maximum 	5.76 Mbit/s
<ul style="list-style-type: none"> for LTE transmission / with downlink / maximum 	100 Mbit/s
<ul style="list-style-type: none"> for LTE transmission / with uplink / maximum 	50 Mbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> for internal network 	4
<ul style="list-style-type: none"> for external network 	2
number of electrical connections	
<ul style="list-style-type: none"> for power supply 	2
type of electrical connection	
<ul style="list-style-type: none"> for internal network 	RJ45 port (10/100 Mbit/s, TP, autocrossover)
<ul style="list-style-type: none"> for external antenna(s) 	SMA antenna socket (50 ohms)
<ul style="list-style-type: none"> for power supply 	Terminal strip
WAN connection	
type of wireless network / is supported	LTE, UMTS, GSM
type of mobile wireless service / is supported	GPRS, eGPRS, HSPA+
operating frequency / for GSM transmission	850 MHz, 900 MHz, 1800 MHz, 1900 MHz
operating frequency / with UMTS transmission	850 MHz, AWS-1 (1700/2100) MHz, 1900 MHz
operating frequency / for LTE transmission	700 MHz, 850 MHz, AWS-1 (1700/2100) MHz, 1900 MHz
supply voltage, current consumption, power loss	
supply voltage / rated value	24 V
supply voltage / rated value	10.8 ... 28.8
type of voltage / of the supply voltage	DC
consumed current	
<ul style="list-style-type: none"> at rated supply voltage / maximum 	330 mA
power loss [W]	
<ul style="list-style-type: none"> maximum 	8 W
ambient conditions	
ambient temperature	

<ul style="list-style-type: none"> during operation 	-20 ... +70 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
depth	127 mm
height	147 mm
width	35 mm
fastening method	
<ul style="list-style-type: none"> 35 mm top hat DIN rail mounting 	Yes
<ul style="list-style-type: none"> S7-300 rail mounting 	Yes
<ul style="list-style-type: none"> S7-1500 rail mounting 	Yes
<ul style="list-style-type: none"> wall mounting 	Yes
product features, product functions, product components / general	
product function	
<ul style="list-style-type: none"> DynDNS client 	Yes
<ul style="list-style-type: none"> no-ip.com client 	Yes
product functions / management, configuration, engineering	
product function	
<ul style="list-style-type: none"> CLI 	Yes
<ul style="list-style-type: none"> web-based management 	Yes
<ul style="list-style-type: none"> MIB support 	Yes
<ul style="list-style-type: none"> TRAPs via email 	Yes
protocol / is supported	
<ul style="list-style-type: none"> Telnet 	Yes
<ul style="list-style-type: none"> HTTP 	Yes
<ul style="list-style-type: none"> HTTPS 	Yes
type of configuration	Web-based management
product functions / diagnostics	
protocol / is supported	
<ul style="list-style-type: none"> SNMP v1 	Yes
<ul style="list-style-type: none"> SNMP v2 	Yes
<ul style="list-style-type: none"> SNMP v2c 	Yes
<ul style="list-style-type: none"> SNMP v3 	Yes
product function	
<ul style="list-style-type: none"> statistics Packet Size 	No
<ul style="list-style-type: none"> statistics packet type 	No
<ul style="list-style-type: none"> error statistics 	No
<ul style="list-style-type: none"> SysLog 	Yes
<ul style="list-style-type: none"> packet filter log 	Yes
product functions / DHCP	
product function	
<ul style="list-style-type: none"> DHCP client 	Yes
<ul style="list-style-type: none"> DHCP server - internal network 	Yes
product functions / routing	
router function	
<ul style="list-style-type: none"> NAT (IP masquerading) 	Yes
<ul style="list-style-type: none"> port forwarding 	Yes
<ul style="list-style-type: none"> NAT traversal 	Yes
<ul style="list-style-type: none"> 1:1 NAT 	Yes
<ul style="list-style-type: none"> DNS cache 	Yes
product functions / security	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
<ul style="list-style-type: none"> password protection 	Yes
<ul style="list-style-type: none"> packet filter 	Yes
<ul style="list-style-type: none"> broadcast/multicast/unicast limiter 	No

product function	
<ul style="list-style-type: none"> • broadcast blocking • with VPN connection 	No IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK protocol / is supported	Yes
<ul style="list-style-type: none"> • IPsec tunnel and transport mode 	Yes
key length	
<ul style="list-style-type: none"> • 1 / with IPsec AES / with Virtual Private Network • 2 / with IPsec AES / with Virtual Private Network • 3 / with IPsec AES / with Virtual Private Network • with IPsec 3DES / with Virtual Private Network 	128 bit 192 bit 256 bit 168 bit
type of Internet key exchange / with Virtual Private Network	
<ul style="list-style-type: none"> • main mode • quick mode 	Yes Yes
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
product functions / time	
protocol / is supported	
<ul style="list-style-type: none"> • NTP • SNTP 	Yes Yes
standards, specifications, approvals	
standard	
<ul style="list-style-type: none"> • for EMC • for FM • for safety / from CSA and UL • for hazardous zone / from CSA and UL 	FCC CFR 47, Part 15, Subpart B FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4 UL 60950-1, CAN/CSA C22.2 No. 60950-1-07, UL E115352 Vol. X2 ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
certificate of suitability	
<ul style="list-style-type: none"> • CCC approval 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://www.siemens.com/snst http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

5/11/2022 