

TAA-Compliant Protect It! 6-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Ethernet Protection, Safety Covers

MODEL NUMBER: TLP66NETAA



Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet Surge protection

Package Includes

- TLP66NETAA
- 6-ft. network cable
- Instruction manual with warranty information

Description

Tripp Lite's TLP66NETAA is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. It has 6 outlets, a 6-ft. cord and diagnostic LEDs. The TLP66NETAA has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft network cable included). \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

OVERVIEW



| | |
|--|---|
| UPC Code | 037332161123 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Cord Gauge Type | 14 gauge; SJT |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 6 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 1.83 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (6) 5-15R |
| Circuit Breaker (amps) | 15 |
| Overload Protection | 15A resettable illuminated combo switch / circuit breaker |
| Transformer Accommodation | (4) Yes |
| Outlet Orientation | Block style with two rows of 3 outlets |
| Right-Angle Outlets | Yes |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Switches | Combination AC circuit breaker and 2-position red illuminated on/off power switch |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 1080 |
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| UL1449 Let Through Rating | 400v |
| EMI / RFI Filtering | Up to 40 dB |
| Automatic Shut-Off | No |
| DATALINE SURGE SUPPRESSION | |



| | |
|--|--|
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | Yes |
| Telephone/DSL Protection | No |
| PHYSICAL | |
| Material of Construction | Plastic |
| Color | Light Gray |
| Power Cord Color | Light Gray |
| Housing Color | Light Gray |
| Mounting Holes or Slots | Yes |
| Receptacle Color | Gray |
| Shipping Dimensions (hwd / cm) | 17.53 x 5.08 x 28.19 |
| Shipping Dimensions (hwd / in.) | 6.90 x 2.00 x 11.10 |
| Shipping Weight (kg) | 0.82 |
| Shipping Weight (lbs.) | 1.80 |
| Unit Dimensions (hwd / in.) | 1.5 x 4.23 x 8.29 |
| Unit Dimensions (hwd / cm) | 3.81 x 10.74 x 21.06 |
| Unit Weight (lbs.) | 1.32 |
| Unit Weight (kg) | 0.60 |
| FEATURES & SPECIFICATIONS | |
| Antimicrobial | No |
| Rotatable Outlets | No |
| STANDARDS & COMPLIANCE | |
| Industry Canada (Communications) | Industry Canada |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 Ultimate Lifetime Insurance |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>