

Cable - CABLE-FCN40/1X50/ 0,5M/IP/MEL - 2903476

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Round cable set for Mitsubishi Electric MELSEC L, MELSEC Q with 1 x Fujitsu connector (40-position) on 1 x IDC/FLK socket strip (50-position), Cable length: 0.5 m



RoHS

Key Commercial Data

Packing unit	1 STK
Custom tariff number	85444290
Country of origin	Germany

Technical data

General

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A
Max. total current of all branches	2 A
Max. conductor resistance	0.16 Ω /m
Length of cable	0.5 m
Single wire, cross section	0.14 mm ²
Single wire, cross section [AWG]	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	8.7 mm
Shielding	no
Outer sheath, material	PVC
External sheath, color	RAL7035

Environmental conditions

Cable - CABLE-FCN40/1X50/ 0,5M/IP/MEL - 2903476

Technical data

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Flame resistance	IEC 60332-1
	DIN VDE 0482 Part 332-1
Resistance to oil	DIN VDE 0472 Part 803, test type B
Gasoline resistance	Against occasional splashes

Connector, module side

Connection name	Field level
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	50
Pitch	2.54 mm

Connector, controller side

Connection name	Controller level
Connection method	Fujitsu connector
Number of connections	1
Number of positions	40

Supported controller

Controller	MITSUBISHI MELSEC Q
- suitable I/O card	QX71
	QX72
	QX82
	QX82-S1
Controller	MITSUBISHI MELSEC L
- suitable I/O card	LX41C4
	LX42C4
Controller	Honeywell MasterLogic 200
- suitable I/O card	2MLI-D24A
	2MLI-D28B
	2MLF-SOEA

Standards and Regulations

Standards/regulations	DIN EN 60352-4
	DIN EN 60603-1
Resistance to oil	DIN VDE 0472 Part 803, test type B
Flame resistance	IEC 60332-1

Cable - CABLE-FCN40/1X50/ 0,5M/IP/MEL - 2903476

Technical data

Standards and Regulations

	DIN VDE 0482 Part 332-1
--	-------------------------

Color code

Connector 1 = connector 2 (optional) = wire color	Fujitsu40 (B1) = IDC/FLK50 (11) = black
	Fujitsu40 (B2) = IDC/FLK50 (48) = brown
	Fujitsu40 (A5) = IDC/FLK50 (46) = red
	Fujitsu40 (B5) = IDC/FLK50 (22) = orange
	Fujitsu40 (A6) = IDC/FLK50 (45) = yellow
	Fujitsu40 (B6) = IDC/FLK50 (21) = green
	Fujitsu40 (A7) = IDC/FLK50 (44) = blue
	Fujitsu40 (B7) = IDC/FLK50 (20) = violet
	Fujitsu40 (A8) = IDC/FLK50 (43) = gray
	Fujitsu40 (B8) = IDC/FLK50 (19) = white
	Fujitsu40 (A9) = IDC/FLK50 (42) = white-black
	Fujitsu40 (B9) = IDC/FLK50 (18) = white-brown
	Fujitsu40 (A10) = IDC/FLK50 (41) = white-red
	Fujitsu40 (B10) = IDC/FLK50 (17) = white-orange
	Fujitsu40 (A11) = IDC/FLK50 (40) = white-yellow
	Fujitsu40 (B11) = IDC/FLK50 (16) = white-green
	Fujitsu40 (A12) = IDC/FLK50 (39) = white-blue
	Fujitsu40 (B12) = IDC/FLK50 (15) = white-violet
	Fujitsu40 (A13) = IDC/FLK50 (34) = white-gray
	Fujitsu40 (B13) = IDC/FLK50 (10) = brown-black
	Fujitsu40 (A14) = IDC/FLK50 (33) = brown-red
	Fujitsu40 (B14) = IDC/FLK50 (9) = brown-orange
	Fujitsu40 (A15) = IDC/FLK50 (32) = brown-yellow
	Fujitsu40 (B15) = IDC/FLK50 (8) = brown-green
	Fujitsu40 (A16) = IDC/FLK50 (31) = brown-blue
	Fujitsu40 (B16) = IDC/FLK50 (7) = brown-violet
	Fujitsu40 (A17) = IDC/FLK50 (30) = brown-gray
	Fujitsu40 (B17) = IDC/FLK50 (6) = brown-white
	Fujitsu40 (A18) = IDC/FLK50 (29) = green-black
	Fujitsu40 (B18) = IDC/FLK50 (5) = green-brown
	Fujitsu40 (A19) = IDC/FLK50 (28) = green-red
	Fujitsu40 (B19) = IDC/FLK50 (4) = green-orange
	Fujitsu40 (A20) = IDC/FLK50 (27) = green-blue
	Fujitsu40 (B20) = IDC/FLK50 (3) = green-violet

Cable - CABLE-FCN40/1X50/ 0,5M/IP/MEL - 2903476

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 6.0	27249205
eCl@ss 7.0	27249205
eCl@ss 8.0	27249205
eCl@ss 9.0	27242220

ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC000237

UNSPSC

UNSPSC 6.01	26121620
UNSPSC 7.0901	26121620
UNSPSC 11	26121620
UNSPSC 12.01	26121620
UNSPSC 13.2	26121620

Approvals

Approvals

Approvals

EAC / UL Listed / cUL Listed / cULus Listed


Ex Approvals

Approval details

EAC RU C-DE.A*30.B00767

Cable - CABLE-FCN40/1X50/ 0,5M/IP/MEL - 2903476

Approvals

UL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cUL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cULus Listed 