



Fuse module, 6 fuse cartridges for 5x20 micro-fuses, Individually switched, Screw connection, Mounting type: Mounting rail TS 35

### Business data

Article number	5714.2
Article name	SM 6-E
GTIN (EAN)	4044211069193
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	103.8 g
Weight per piece (including packaging)	131.55 g
Unit of weight	G
Customs number	85363010
Country of origin	NL
Product description	Fuse modules

### Technical data

#### Dimensions

Length	87 mm
Width	47 mm
Height TS 35/7.5	77 mm

#### Ratings

Current load, max.	6,3 A
Overvoltage category	III
Contamination degree	2

#### Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	4 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Stripping length	7 mm
Torque	0.6 Nm

#### Input data

Max. operating voltage AC/DC	250 V
Current load per channel, max.	4 A
Number of channels	6

#### Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

#### Further technical data

Fuse size	5x20 mm
-----------	---------

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Approvals

---

#### Standards and regulations

---

Standards / specifications

DIN VDE 0110 / EN 50178

---

---

**Media**

---

---

**Accessories**

---